

SPL Iron - Studijski kompresor

SPL Iron - Studijski kompresor

Šifra: 12313

Kategorija proizvoda: Kompresori / Limiteri

Proizvođač: SPL

Cena: **479.880,00** rsd

Kompleksno ispravljačko kolo koje menja attack, release (times) & curves i opšte ponašanje; ovo ispravljačko kolo čini kompresor istinski raznolikim, i prilagodljivim raznim vrstama materijala/programa. Cevni prednapon, tu je za veću minute kontrolu.

Što se tiče povezivosti, **IRON** ima izbalansirane I/O terminale, kao i ¼"-ne ulaze za džekove sa strane.

Sidechain EQ (filter) - allows you to choose between off, four sidechain-filter presets, or an external sidechain signal

Mu-Metal iron transformers

Compression behavior of the tubes can be adapted to program material with tube bias (with three different settings), ±12 dB input gain, and threshold control

Six different rectifier settings available with different diodes (germanium, silicon, LED, mixed)

In Link mode, the threshold, tube bias, attack, release, and rectifier parameters, as well as the sidechain EQs, are controlled with the right side (channel 2) of the unit

Additional passive 120V equalizer with two presets (AirBass and Tape Roll-Off)

Interval control in Auto Bypass mode helps compare the original and compressed signals

High dynamic 120V operating voltage

Suitable for subgroups and mastering studios

Designed, developed, and manufactured in Germany

Frequency Range: 10 Hz to 40 kHz (40 kHz = -3 dB)

CMRR: At 0 dBu, 1 kHz: >80 dB; 10 kHz: >65 dB

THD & Noise: >82 dB at 0 dBu

Noise: A-Weighted: -98 dBu

Total Harmonic Distortion: 0.06% @ 1 kHz / -10 dBu, 0.01 % @ 1 kHz / 0 dBu, 0.002% @ 1kHz / +10 dBu

Input Impedance: 20 Kilohms

Input Level: +32.5 dBu, Maximum

Output Impedance: <50 Ohms

Output Level: +32.5 dBu, Maximum

Power Consumption: 45 W, Maximum

Fuses: 230 V / 50 Hz: 1 A, 115 V / 60 Hz: 2 A

Dimensions: 48.2 x 17.7 x 31.2 cm, Weight: 11.0 kg