

## MARTIN WISMAN SPX 250 B-Stock

Šifra: 8140  
 Kategorija proizvoda: Pasivne Zvučne Kutije  
 Proizvođač: Martin Wisman

**Cena: 25.080,00 rsd**

### MARTIN WISMAN SPX 250 B-Stock

High

Impact Molded Polypropylene Enclosure  
 10L250-82 10 LF Transducer  
 1.4"Voice Coil, 1 Exit Titanium  
 Compression Driver  
 Smooth Response With High Power  
 Handling Capacity (Continuous Program/RMS),  
 1000W/250W  
 5 Integral Suspension Points  
 Complete Mounting Solutions

### General Description and Applications:

The SPX 250 features a molded polypropylene enclosure that it inherently weather resistant. MARTIN WISMAN audio used advanced program techniques to create the most successful and influential professional speaker system. High power, efficiency, lower distortion and great low frequency extension provide an unbelievable performance. SPX 250 can be used for live sound reinforcement, vocals, speech and music playback in entertainment, schools, pub, coffee shop and outdoor venues. Portability is one of the important factors for choice especially. For permanent suspension or attaching brackets, the SPX 250 also has two M8 inserts on the top and bottom, two on the side, for a total of 5.

### Technical Specifications

<b>Freq. Range (-10dB):</b>	60Hz~20kHz
<b>Freq. Response (-3dB):</b>	70Hz~20kHz
<b>Rec.Hipass Frequency:</b>	30Hz
<b>Axial Sensitivity:</b>	95dB(1W/1m)
<b>Max Calculated SPL:</b>	125dB
<b>Rated System Power:</b>	250W Continuous 1000W Peak
<b>LF Transducer:</b>	10"/65mm
<b>HF Transducer:</b>	1"34mm
<b>Crossover Frequency:</b>	2.0kHz
<b>Nominal Impedance:</b>	8 Ohms
<b>Connector:</b>	2 x NL4 Speakon
<b>Dim (HxWxD):</b>	557mmx332mmx313mm
<b>Net Weight:</b>	16Kg
<b>Shipping Weight:</b>	18Kg
<b>Horizontal Clearance:</b>	800