

## ORTOFON PRO S REPLACEMENT STYLUS

ORTOFON PRO S REPLACEMENT STYLUS

Šifra: 2970

Kategorija proizvoda: DJ Igle i Kertridži za Gramofone

Proizvođač: Ortofon

Cena: **3.120,00** rsd

### Entry-level cartridge for all-purpose use

New DJ? This entry-level cartridge is perfect for newcomers on the DJ scene who want to start off with decent, but not too expensive equipment.

The Pro S has a spherical diamond stylus which minimizes scratching and a solid cantilever which can survive hectic activity at the turntable.

No matter what the application, the Pro S provides remarkable versatility for virtually any setting.

**The sound quality is absolutely not to worry about. The Pro S is a consistent performer and a fine all-rounder!**

|  |                       |
|--|-----------------------|
| Output voltage at 1000Hz, 5cm/sec.                       | 5 mV                  |
| Channel balance at 1kHz                                  | 2 dB                  |
| Channel separation at 1kHz                               | 20 dB                 |
| Channel separation at 15 kHz                             | 15 dB                 |
| Frequency range at -3dB                                  | 20-20.000 Hz          |
| Frequency response                                       | 20-18.000 Hz +/- 2 dB |
| Tracking ability at 315 Hz at recommended tracking force | 70 µm                 |
| Compliance, dynamic lateral                              | 7 µm/m N              |
| Stylus type  | Spherical             |
| Stylus tip radius  | R 26 µm               |
| Tracking force range                                     | 3,0-5,0 g (30-50 mN)  |
| Tracking force recommended                               | 4,0 g (40 mN)         |
| Tracking angle   | 20°                   |
| Internal impedance, DC resistance                        | 750 Ohm               |
| Internal inductance                                      | 450 mH                |
| Recommended load resistance                              | 47 kOhm               |
| Recommended load capacitance                             | 200-600 pF            |
| Cartridge weight   | 18,5 g                |