

SUPERLUX E525 Long

## SUPERLUX E525 Long

Šifra: 1069  
Kategorija proizvoda: Mikrofoni Za Kamere  
Proizvođač: SUPERLUX

Cena: **11.400,00** rsd

### E525 S/L

Stereo Condenser Shotgun Microphone

The E525 is a stereo condenser shotgun microphone with figure 8 side microphone for MS stereo recording. It has 4-output formats for MS, XYwide, XY-narrow and Mono. The E525 is suitable for location, film, EFP and theater sound pick up or SNG/ENG program use.

E525L: long 380 mm

### Features

2 stereo record modes, MS& XY(W/N)

Output signals are original from supercardioid and figure-8 capsule, not maxtrix decoded yet  
Exceptional off-axis suppression  
Aluminum alloy, light weight

Exter  
Very

### Applications

Film

EFP  
SNG  
Live Sound

ENG  
Theat

**Type:** Back electret, Ø14 mm (Ø0.55")

**Polar Pattern:** MS/XY stereo shotgun

**Output Signal:** original from supercardioid and figure-8 capsule, not maxtrix decoded yet

**Frequency Response:** 20-20,000

**Low Frequency Filter:** 100 Hz, 12 dB/oct

**Sensitivity:** -34 dBV/Pa (9.0 mV)

**Output Impedance:** 200 Ω

**Min. Load Impedance:** 1,000 Ω

**S/N Ratio:** 72 dB

**Equivalent Output Noise:** 22 dB

**Max. SPL:** 127 dB SPL

**Dynamic Range:** 105 dB

**Power Requirements:** 12-52V

**Finish:** Titanium grey

**Connector:** XLR5M

**Dimensions:**

E525S: Ø21.5 × 235 mm (Ø0.85" × 9.3")

e525L: Ø21.5 × 380 mm (Ø0.85" × 14.97")

**Net Weight:**

E525S: 103 g (3.6 oz)

E525L: 153 g (5.4 oz)

**Accessories Furnished:**

E525S: S32 windscreen

E525L: S33 windscreen

HM40C camera mic shock mount, HM37S mic clip with screw knob, YA2 threaded adapter, FM0.6AMM, 0.6-meter cable with XLR5F~2 × XLR3M connector, pouch

Optional Accessories: HM35 shock mount; HM35C camera microphone shock mount

Packaging: Hand carrying bag, colorful outer packaging

