

SUPERLUX E525 Long

Šifra: 1069
Kategorija proizvoda: Mikrofoni Za Kamere
Proizvođač: SUPERLUX

Cena: **15.840,00** rsd

E525 S/L

Stereo Condenser Shotgun Microphone

The E525 is a stereo condenser shotgun microphone with figure 8 side microphone for MS stereo recording. It has 4-output formats for MS, XYwide, XY-narrow and Mono. The E525 is suitable for location, film, EFP and theater sound pick up or SNG/ENG program use.

E525L: long 380 mm

Features

2 stereo record modes, MS& XY(W/N)

Output signals are original from supercardioid and figure-8 capsule, not maxtrix decoded yet
Exceptional off-axis suppression
Aluminum alloy, light weight

Exter
Very

Applications

Film

EFP
SNG
Live Sound

ENG
Theat

Type: Back electret, Ø14 mm (Ø0.55")

Polar Pattern: MS/XY stereo shotgun

Output Signal: original from supercardioid and figure-8 capsule, not maxtrix decoded yet

Frequency Response: 20-20,000

Low Frequency Filter: 100 Hz, 12 dB/oct

Sensitivity: -34 dBV/Pa (9.0 mV)

Output Impedance: 200 Ω

Min. Load Impedance: 1,000 Ω

S/N Ratio: 72 dB

Equivalent Output Noise: 22 dB

Max. SPL: 127 dB SPL

Dynamic Range: 105 dB

Power Requirements: 12-52V

Finish: Titanium grey

Connector: XLR5M

Dimensions:

E525S: Ø21.5 × 235 mm (Ø0.85" × 9.3")

e525L: Ø21.5 × 380 mm (Ø0.85" × 14.97")

Net Weight:

E525S: 103 g (3.6 oz)

E525L: 153 g (5.4 oz)

Accessories Furnished:

E525S: S32 windscreen

E525L: S33 windscreen

HM40C camera mic shock mount, HM37S mic clip with screw knob, YA2 threaded adapter, FM0.6AMM, 0.6-meter cable with XLR5F~2 × XLR3M connector, pouch

Optional Accessories: HM35 shock mount; HM35C camera microphone shock mount

Packaging: Hand carrying bag, colorful outer packaging

