



**Cena: 19.080,00 rsd**

### Features

- Fan-cooled
- 3 Mic and 3 Aux inputs
- 70 V, 100 V PA-outputs
- 1 Mic-connection on the front panel, Chime button
- Treble and bass control
- Master-control
- Protection-circuits: over current,
- Screw terminals of 6 zone outputs

- 1 Line-output
- 4-16 Ohms output for connecting a passive speaker-system monitor
- Build in Mp3 player with songs name display
- 7-fold level indicator
- 19"-dimensions
- short circuit, turn-on delay

### Specifications

MODEL	TPU-3060	TPU-3120	TPU-3180 Z6	TPU-3250	TPU-3300
<b>Power supply</b>	AC110V~ 60 Hz	AC110V~ 60 Hz	AC110V~ 60 Hz	AC110V~ 60 Hz	AC110V~ 60 Hz
<b>Output power</b>	60W RMS	120W RMS	180 W RMS	250 W RMS	300 W RMS
<b>Output type</b>	70 V, 100 V or 4-16	70 V, 100 V or 4-16	70 V, 100 V or 4-16	70 V, 100 V or 4-16	70 V, 100 V or 4-16
<b>Outputcurrent at 70V</b>	0.9A	1.4A	2.5 A	3.6 A	5.0 A
<b>Output current at 100 V</b>	0.6A	1.0A	1.8 A	2.5 A	3.6 A
<b>Mic input</b>	5 mV, 600 Ohms	5 mV, 600 Ohms	5 mV, 600 Ohms	5 mV, 600 Ohms	5 mV, 600 Ohms
<b>Line input</b>	300 mV, 10 kOhms	300 mV, 10 kOhms	300 mV, 10 kOhms	300 mV, 10 kOhms	300 mV, 10 kOhms
<b>Frequency range</b>	80 Hz - 16 kHz	80 Hz - 16 kHz	80 Hz - 16 kHz	80 Hz - 16 kHz	80 Hz - 16 kHz
<b>Distortion</b>	0.5 % (1 kHz)	0.5 % (1 kHz)	0.5 % (1 kHz)	0.5 % (1 kHz)	0.5 % (1 kHz)
<b>Signal/Noise ratio:</b>	Aux	85 dB	85 dB	85 dB	85 dB
	Mic	75 dB	75 dB	75 dB	75 dB
<b>FUSE</b>	T2A/250V	T2A/250V	T2A/250V	T5A/250V	T5A/250V
<b>Carton dimensions</b>	535X375X175mm	550X425X180mm	550X425X180mm	550X455X180mm	550X455X180mm
<b>Weight</b>	0.25kg	1.1kg	1.2kg	1.4kg	1.6kg