

## Biamp - Apart KUBO5T-W - Nazidni zvučnik

Šifra: 12598

Kategorija proizvoda: Nazidni Zvučnici

Proizvođač: Biamp - Apart

Cena: **14.280,00** rsd

The stylish and subtle cube-shaped designed KUBO5T is a 5.25" two-way compact loudspeaker with bass reflex port. It can be used as a 70/100 volt or low impedance 16 ohms loudspeaker producing up to 80 watts dynamic power. The K-Mount bracket offers easy cable management and 140° vertical or horizontal mounting flexibility. Combined with the special designed fixing K-bolts you can install the loudspeaker in a safe and comfortable way on any type of wall or ceiling. Easy daisy chaining of multiple KUBO loudspeakers can be done via the in & link connection with euroblock connectors. The installer friendly end-caps, held in place by 14 integrated strong neodymium magnets, hide all connections and bracket hardware on both sides. This top-notch product offers amazing sound quality and performance in a discrete and neutral housing fitting any kind of interior.

<b>height</b>	155 mm	<b>width</b>	164 mm
<b>depth</b>	136 mm	<b>loudspeaker system</b>	2-way
<b>woofer size</b>	5.25 inch	<b>woofer cone material</b>	coated paper
<b>tweeter size</b>	1 inch	<b>mounting system</b>	U-bracket
<b>100V transformer power taps</b>	30 - 15 - 6 - 3 watts	<b>70V transformer power taps</b>	30 - 15 - 7.5 - 3 - 1.5 watts
<b>impedance (ohms)</b>	16	<b>low impedance dynamic power</b>	80 watts
<b>low impedance RMS power</b>	50 watts	<b>SPL 1W/1m</b>	92 dB
<b>max SPL 1m</b>	106 dB	<b>frequency response</b>	94 - 20K Hz
<b>main construction material</b>	ABS plastic	<b>grille main material</b>	steel
<b>IP rating</b>	40	<b>Horizontal dispersion angle 1000 Hz</b>	180°
<b>Vertical dispersion angle 1000 Hz</b>	180°	<b>closest RAL colour (subject to deviations)</b>	RAL9016 (W) / RAL9011 (BL)
<b>Net weight product (kg)</b>	2.05		