

Biamp - Apart MASK 6C-W**Biamp - Apart MASK 6C-W**

Šifra: 12898

Kategorija proizvoda: Outdoor Zvučnici

Proizvođač: Biamp - Apart

Cena: **20.280,00** rsd

The MASK6C low impedance loudspeaker has a unique design and delivers a crystal clear sound for background sound up to dance level music. The cabinet is made of high quality enforced PP4 ABS, with an aluminium grill. The design of the MASK6C ensures high quality and long lasting performance in indoor and outdoor use, even under extreme weather conditions. The MASK6C has a powerful 6.5" coated paper cone woofer and a 1" silk dome tweeter which results in a high SPL and extremely low distortion. This ensures an unprecedented clarity over the whole frequency spectrum. The built-in Apart 3-step protection and the high-quality components make the MASK6C an ultra- reliable, fail safe loudspeaker even at high power loads. Thanks to the revolutionary design of the ClickMount bracket, the MASK6C is without a doubt the fastest and most installer friendly loudspeaker to-date. The pre-defined clicks on the ClickMount ensure a perfect alignment for every loudspeaker. With the discrete cable management system, integrated spirit level and in/out connectors, the full cabling is done on the bracket. To complete the installation simply click the loudspeaker on the ClickMount!

| | | | |
|-----------------------------------|-------------|--|----------------------------|
| height | 328 mm | width | 198 mm |
| depth | 190 mm | loudspeaker system | 2-way |
| woofer size | 6,5 inch | woofer cone material | coated paper |
| tweeter size | 1 inch | mounting system | clickmount |
| impedance (ohms) | 8 | low impedance dynamic power | 200 watts |
| low impedance RMS power | 150 watts | SPL 1W/1m | 90 dB |
| max SPL 1m | 110 dB | frequency response | 65 - 20k Hz |
| main construction material | ABS plastic | grille main material | aluminium |
| IP rating | 64 | Horizontal dispersion angle 1000 Hz | 180° |
| Vertical dispersion angle 1000 Hz | 180° | closest RAL colour (subject to deviations) | RAL9016 (W) / RAL9011 (BL) |
| Net weight product (kg) | 3.35 | | |