

Biamp - Apart MASK 6CT-BL

Šifra: 12743

Kategorija proizvoda: Outdoor Zvučnici

Proizvođač: Biamp - Apart

Cena: **22.680,00** rsd

The time saving click mount system enables all installation cabling to be completed at the mounting bracket and the speaker is simply clicked into place at final fix.

The MASK6CT background music loudspeaker benefits from a stylish innovative design and are rated at 150 watts RMS when used in low impedance 16 ohms (up to 4 loudspeakers in parallel on a standard 4 ohms amplifier channel) or 60 watts in 100 volt line systems. Power tapings of 60, 30,15 & 6 watts are selected via a rotary switch on the back.

The powerful 6.5" woofer and Ferro-fluid cooled 1" silk dome tweeter offers high SPL and ultra low distortion. The internal bracketing and shape of the cabinet avoids internal interference and optimises the sound quality.

Built in auto-reset overload protection - 3-step Protection Guard is effective even at high power loads. Suitable for use either indoors or outdoors, supplied with wall mounting bracket and available in black, MASK6CT-BL or white, MASK6CT-W.

| | |
|-------------------------------------|------------------------|
| height | 38 mm |
| width | 198 mm |
| depth | 190 mm |
| loudspeaker system | 2-way |
| woofer size | 6,5 inch |
| woofer cone material | coated paper |
| tweeter size | 1 inch |
| mounting system | clickmount |
| 100V transformer power taps | 60 - 30 - 15 - 6 watts |
| impedance (ohms) | 16 |
| low impedance dynamic power | 200 watts |
| low impedance RMS power | 150 watts |
| SPL 1W/1m | 90 dB |
| max SPL 1m | 110 dB |
| frequency response | 65 - 20K Hz |
| main construction material | ABS plastic |
| grille main material | aluminium |
| IP rating | 64 |
| Horizontal dispersion angle 1000 Hz | 180° |
| Vertical dispersion angle 1000 Hz | 180° |
| Net weight product (kg) | 3.9 |

<https://www.commercialaudiosolutions.com/fileuploader/download/download/?d=0&file=custom%2Fupload%2F1521627455.pdf>