

ARCAM SA10 Integrisano Pojačalo

This

Šifra: 13497
 Kategorija proizvoda: Integrisana Pojačala
 Proizvođač: ARCAM



Cena: 95.880,00 rsd

Integrated amplifier works hard to maintain excellent stereo separation in order to achieve a wide and deep musical sound stage, all while minimising the interference. The SA10 Integrated amplifier features both a pre amplifier and a power amplifier for source switching, volume control and superior amplification.

A singer's sharp intake of breath before hitting the chorus, a guitarist's fingers sliding against the strings - it's those seemingly minor details that can bring music to life. Fish out one of your all-time favourite albums and play it through a Bluetooth speaker, and guess what? Its sounds like a Bluetooth speaker. Play it through the SA10, and it's as close to hearing the artist's performance as you're likely to get. There's always joy in digging out an old recording you haven't heard in years. With the HDA range, it'll feel like hearing it for the first time.

- Extremely efficient class A/B amplification
- 50W of power per channel
- 5 analogue inputs including phono
- 3 digital inputs
- 32-bit DAC, Sabre ESS9016K2M
- Full I/P control
- Total harmonic distortion + noise = 0.003%

Both Channels, 8Ω, 20Hz—20kHz	50W
Single Channel, 4Ω, at 1kHz	90W
Harmonic Distortion, 80% Power, 8Ω at 1kHz	0.003%
Input Sensitivity At 1kHz	5mV
Input Impedance	47kΩ + 100pF
Frequency Response (ref. RIAA curve)	20Hz - 20kHz ± 1dB

Signal/Noise Ratio (A-wtd) 50W, ref. 5mV Input	80dB
Overload Margin, Ref. 5mV at 1kHz	21dB
Nominal Sensitivity	1V
Input Impedance	10k Ω
Maximum Input	6Vrms
Frequency Response	20Hz - 20kHz \pm 0.2dB
Signal/Noise Ratio (A-wtd) 50W, ref. 1V Input	106dB
DAC	ESS9016K2M
Frequency Response	20Hz - 20kHz \pm 0.05dB
Total Harmonics Distortion + Noise	0.0007%
Signal/Noise Ratio (A-wtd)	115dB
Supported Sample Rates (Optical)	32kHz, 44.1kHz, 48kHz, 88.2kHz, 96kHz
Supported Sample Rates (Coaxial)	32kHz, 44.1kHz, 48kHz, 88.2kHz, 96kHz, 176.4kHz, 192kHz
Bit Depth	16-bit - 24-bit
Nominal Output Level	630mV
Output Impedance	230 Ω
Maximum Output Level Into 600Ω	5Vrms
Output Impedance	1 Ω
Load Range	16 Ω - 2k Ω
Mains Voltage	110-120V or 220-240V, 50-60Hz
Maximum Power Consumption	350W
Dimensions W x H x D (including feet, control knob and speaker terminals)	433 x 87 x 310mm
Weight (Net)	8.4kg
Weight (Gross)	10.7kg

Supplied Accessories

Mains leads
Remote control
2 x AAA batteries