

ART DUALXDirect - DI Box

Šifra: 16879

Kategorija proizvoda: DI Box i Phantom Power

Proizvođač: ART

Cena: **9.480,00** rsd

The inputs are on 1/4"/XLR combo jacks, and the outputs on balanced XLR connectors. Each channel has a ground lift switch for reducing hum and ground-loop noise, and an input attenuator switch that pads the signal coming in by 30 dB. A pair of 1/4" Thru jacks let you simultaneously pass your source signal through to an amp or other device.

The DUALXDirect runs on the phantom power of the device connected to its output. If those aren't available, a 9V battery (included) supplies the juice.

Fully active design

Phantom voltage or 9V battery powered

Converts high-impedance balanced/unbalanced inputs into 600Ω balanced outputs

Switchable input attenuation (0, -30 dB)

Switchable ground lift

1/4" TRS / XLR combo connector inputs

Balanced outputs on XLR connectors

Rugged extruded aluminum case

ART DUALXDirect Specs

Type Active Dual

Inputs 2 x 1/4" TRS / XLR Combo (balanced/unbalanced) 470k Ω

Output Connectors 2 x XLR male 600 Ω

2 x 1/4" TRS phone (pass-through)

Dynamic Range > 100 dB (typical)

Channel Separation > 80 dB (typical)

Maximum Input Level +4, +34 dBu

Maximum Output Level +6 dBu (battery powered), +14 dBu (phantom powered)

Output Impedance 600 Ω

Frequency Response 10 Hz - 100 kHz, \pm 0.5 dB @ +0 dBu

THD <.05%(typical)

Channel Separation > 80 dB (typical)

Controls 2 x Low-Pass Filter (switchable); -3 dB @ 30 kHz

2 x Input Attenuation (switchable); (0, -30 dB)

2 x Phase Invert (switchable)

2 x Ground Lift (switchable)

Power Requirements 9V @ 7.5 mA (battery, alkaline recommended), 18 - 48V DC @ 6.4 mA (phantom power per channel)

Dimensions 4.6 x 3.9 x 1.85" (117 x 99 x 47 mm)

Weight 0.84 lbs (0.38 kg)

Packaging Info

Package Weight 1 lb

Box Dimensions (LxWxH) 13.3 x 6.6 x 0.4"