

ART PRO AUDIO DJPRE II Gramofonsko Pretpojačalo

Šifra: 301
Kategorija proizvoda: Gramofonska Pretpojačala
Proizvođač: ART

Cena: 7.920,00 rsd



The
DJ
PRE II

(formerly named the "Phono MicroPRE") acts as an interface between your turntable and your audio recording / playback system. The analog input capacitance can be switched between 100pF and 200pF to optimize your phono cartridge response. A switchable low cut filter removes turntable rumble while leaving the audio pristine. The front gain trim control and signal/clip LED allow you to optimize the preamp's gain for a wide range of input sources. The built-in low noise phono preamp circuitry is highly accurate and precisely conforms to the RIAA standard. The line output jacks are low impedance and can be used with any sound card.

Housed in an all aluminum black anodized case, the DJ PRE II can be powered by a wide variety of external supplies. If you need to amplify and EQ your vinyl records to interface with your audio workstation, sound card, home stereo system or main monitor system, the DJ PRE II gives you flawless audio reproduction in a rugged and reliable package.

Features

- High accuracy/low noise preamp
- Variable preamp gain
- Selectable cartridge loading
- Heavy duty extruded chassis

- Switchable low cut rumble filter
- Signal present/clip indicator
- RCA preamp outputs
- Designed and developed in the USA

Specifications

Frequency Response 10Hz -50kHz, +/-0.5dB
Total Harmonic Distortion: .01% Typical @ 1kHz

Input Impedance: 47k Ohms in Parallel with Either 100pF or 200pF

Maximum Gain: 45dB @1kHz

Maximum Output Level: +6dBu (1.4Vrms)

Phono EQ Standard: Conforms to RIAA Curve

Hum and Noise: > 90dB below clipping

Maximum Input Level: 40mVrms @1kHz

In / Out Connections: RCA

Filter Type/Response: Switchable, Low Cut, -3dB @ 22Hz

Power Requirements: 7-12V DC or 9-12V AC
@150mA

Dimensions: 1.85"H x 4.6"W x 4.5"D (47mm x
117mm x 114mm)

Weight: 1.25 lbs (0.57kg)