

## ART PRO AUDIO MX624CE - Višezonska mikseta

Šifra: 10274  
 Kategorija proizvoda: Višezonske Miksete  
 Proizvođač: ART

Cena: **38.400,00** rsd

### Six Channel Stereo Mixer

Six stereo input channels with individual level controls

Balanced mono microphone XLRs available on the first three channels

Full +48V low-noise phantom power independently switchable for each mic input

Front panel 1/8-inch stereo (TRS) mini-phone plug for portable music player input

Two bus input 1/4-inch TRS jacks allow units to be chained to provide extra inputs

Input Connections	XLR female balanced (Mic, channels 1-3) RCA unbalanced (Line Inputs 1-6, Left & Right) 1/4-inch TRS unbalanced stereo (Bus Inputs, Zone 1 & 2)
Output Connections	1/4-inch TS unbalanced (Zone 1 & 2 Out, Left & Right)
Input Impedance	4k Ohms (Mic), 10k Ohms (Line), 10k Ohms (Bus)
Output Impedance	200 Ohms (Zone 1 & 2)
Frequency Response	20 Hz - 20 kHz (+0, -1 dB) (channels 1-6 in, zone out)
Total Harmonic Distortion	<0.01% @ 1 kHz, typical
Phase Response	All connections are phase coherent
Signal to Noise Ratio	>90 dB typical (Ref 0dBu)
CMRR	>43 dB typical
Maximum Input Level	-4 dBu, +16 dBu with 20 dB pad (Mic), >25 dBu (Line)
Maximum Output Level	+20 dBu (unbalanced)
Maximum Gain	57 dB (Mic), 31 dB (Line)

Ducking Threshold	-49.5 dBv (adjustable via rear-panel dipswitches)
Ducking Depth	15 dB
Tone Controls	+/-12 dB @ 100 Hz & 10 kHz
Phantom Power	Switch selectable, +48V DC (regulated and filtered), 7 mA current limiting per leg
Power Requirements	USA: 85-125 VAC, 50-60 Hz, <15W Export units configured for country of destination
Dimensions	1.75"H x 19"W x 6"D (44.5mm x 483mm x 152mm)
Weight	4.9 lbs. (2.2 kg)