

Neutrik NJ3FP6C

## Neutrik NJ3FP6C

Šifra: 13915

Kategorija proizvoda: Konektori

Proizvođač: Neutrik

Cena: **1.020,00** rsd

### Product

Title NJ3FP6C

Connection Type Jack

Gender female

Electrical

Contact resistance < 6 mΩ (initial)

Dielectric strength 1 kVdc

Insulation resistance ≥ 1 GΩ @ 500 V dc

Rated current per contact 10 A

Mechanical

Insertion force < 30 N

Withdrawal force < 20 N

Lifetime > 10000 mating cycles

Locking force > 80 N

Wiresize 1 mm<sup>2</sup>

Wiresize 18 AWG

Wiring Solder contacts

Locking device Latch lock

Mounting direction Front mounting

Chassis shape D

Material

Contact plating 2 μm Ag

Contacts Copper alloy (CuSn6) (Ground)

Insert Polyamide (PA 6.6 30 % GR) UL94 V-0

Shell Zinc diecast (ZnAl4Cu1)

Shell plating Nickel

Strain relief Polyacetal (POM)

Environmental

Standard compliance EIA RS 453, IEC 60603-11

Solderability Complies with IEC 60068-2-20

Temperature range -25 °C to +70 °C