

## MARTIN AUDIO X8B Black - Pasivni zvučnik

Šifra: 13945  
Kategorija proizvoda: Pasivne Zvučne Kutije  
Proizvođač: Martin Audio

**Cena: 47.880,00 rsd**

### MARTIN AUDIO X8B Black - Pasivni zvučnik

#### Features

Ultra-Compact passive two-way system  
Symmetrical multi-angle plywood enclosure  
User-rotatable 90° x 50° horn  
Vertical and horizontal orientation  
Screw-free, cloth-backed perforated steel grille  
Integral ergonomic handle  
Pole-mount bung maintains clean lines  
8Ω nominal impedance  
Twin NL4 connectors  
Flexible mounting options via M8 inserts

#### Applications

Portable sound reinforcement  
Live music clubs  
Bars and restaurants  
Nightclubs  
Unobtrusive stage monitoring  
Corporate AV events and conferences  
Weddings and parties  
Main PA infill  
Secondary stages at festivals  
HoW, leisure centres and retail outlets

As a stand-alone loudspeaker, it has a multitude of professional applications — from distributed sound reinforcement, HoW and AV events to frontfill/infill and use as a micro stage monitor. Complemented by a BlacklineX subwoofer, it is the ideal, simple-to-use system for portable applications and installations which call for an unobtrusive system that can deliver pristine sound over short and medium throw distances.

The Blackline X8 is constructed from plywood and fitted with a screw-free steel grille, M8 inserts for wall brackets and eyebolt suspension, plus a pole-mount socket with a removable bung that maintains clean lines in install applications. Finished in black textured paint.

A full-range passive two-way system, the X8 may be used without a controller. However, the EQ and limiter functions of a controller such as the Martin Audio DX0.5 will maximise its capabilities. When used in conjunction with an X115, X118 or X210 subwoofer, crossover and EQ functions can be performed by the DX0.5.

TYPE Ultra-Compact, passive two-way system  
FREQUENCY RESPONSE (5) 70Hz-20kHz ± 3dB, -10dB @ 60Hz  
DRIVER LF: 8" (200mm)/2" (50mm) voice coil, ferrite motor system  
HF: 1" (25mm) exit/1" (25mm) voice coil, polyimide dome compression driver  
RATED POWER (2) 200W AES, 800W peak  
SENSITIVITY (8) 92dB  
MAXIMUM SPL (9) 115dB continuous, 121dB peak  
NOMINAL IMPEDANCE 8Ω  
DISPERSION (-6DB) 90° H x 50° V (user-rotatable)  
CROSSOVER 2.9kHz passive  
ENCLOSURE Multi-angle birch/poplar ply  
FINISH Black textured paint  
PROTECTIVE GRILLE Black perforated steel with scrim cloth backing

CONNECTORS 2 x NL4 type

PIN CONNECTIONS (INPUT) 1+/-1-

PIN CONNECTIONS (LINK) 1+/- to 1+/-

FITTINGS 13 x M8, 6 x M6 inserts, pole-mount socket, 1 x pocket handle

DIMENSIONS (W) 257mm x (H) 422mm x (D) 243mm

(W) 10.1ins x (H) 16.6ins x (D) 9.6ins

WEIGHT 8kg (17.6lbs)

ACCESSORIES Wall bracket, eyebolts