

MARTIN AUDIO X8B Black - Pasivni zvučnik

Šifra: 13945

Kategorija proizvoda: Pasivne Zvučne Kutije

Proizvođač: Martin Audio

Cena: **47.880,00** rsd

Features

- Ultra-Compact passive two-way system
- Symmetrical multi-angle plywood enclosure
- User-rotatable 90° x 50° horn
- Vertical and horizontal orientation
- Screw-free, cloth-backed perforated steel grille
- Integral ergonomic handle
- Pole-mount bung maintains clean lines
- 8Ω nominal impedance
- Twin NL4 connectors
- Flexible mounting options via M8 inserts

Applications

- Portable sound reinforcement
- Live music clubs
- Bars and restaurants
- Nightclubs
- Unobtrusive stage monitoring
- Corporate AV events and conferences
- Weddings and parties
- Main PA infill
- Secondary stages at festivals
- HoW, leisure centres and retail outlets

As a stand-alone loudspeaker, it has a multitude of professional applications — from distributed sound reinforcement, HoW and AV events to frontfill/infill and use as a micro stage monitor. Complemented by a BlacklineX subwoofer, it is the ideal, simple-to-use system for portable applications and installations which call for an unobtrusive system that can deliver pristine sound over short and medium throw distances.

The Blackline X8 is constructed from plywood and fitted with a screw-free steel grille, M8 inserts for wall brackets and eyebolt suspension, plus a pole-mount socket with a removable bung that maintains clean lines in install applications. Finished in black textured paint.

A full-range passive two-way system, the X8 may be used without a controller. However, the EQ and limiter functions of a controller such as the Martin Audio DX0.5 will maximise its capabilities. When used in conjunction with an X115, X118 or X210 subwoofer, crossover and EQ functions can be performed by the DX0.5.

TYPE Ultra-Compact, passive two-way system

FREQUENCY RESPONSE (5) 70Hz-20kHz ± 3dB, -10dB @ 60Hz

DRIVER LF: 8" (200mm)/2" (50mm) voice coil, ferrite motor system

HF: 1" (25mm) exit/1" (25mm) voice coil, polyimide dome compression driver

RATED POWER (2) 200W AES, 800W peak
SENSITIVITY (8) 92dB
MAXIMUM SPL (9) 115dB continuous, 121dB peak
NOMINAL IMPEDANCE 8Ω
DISPERSION (-6DB) 90° H x 50° V (user-rotatable)
CROSSOVER 2.9kHz passive
ENCLOSURE Multi-angle birch/poplar ply
FINISH Black textured paint
PROTECTIVE GRILLE Black perforated steel with scrim cloth backing
CONNECTORS 2 x NL4 type
PIN CONNECTIONS (INPUT) 1+/1-
PIN CONNECTIONS (LINK) 1+/- to 1+/-
FITTINGS 13 x M8, 6 x M6 inserts, pole-mount socket, 1 x pocket handle
DIMENSIONS (W) 257mm x (H) 422mm x (D) 243mm
(W) 10.1ins x (H) 16.6ins x (D) 9.6ins
WEIGHT 8kg (17.6lbs)
ACCESSORIES Wall bracket, eyebolts