

## MARTIN AUDIO CDD15B - Zvučnik

Šifra: 14936  
Kategorija proizvoda: Nazidni Zvučnici  
Proizvođač: Martin Audio

**Cena: 275.880,00 rsd**

Black or white standard colour options

### Applications

Live Music Clubs and Bars  
Nightclubs  
Bars and Restaurants  
Museums and AV Spaces  
Convention Centres  
Hotels  
Retail Outlets  
Leisure Centres  
Houses of Worship

The Coaxial Differential Dispersion technology employed in the CDD15 delivers more consistent audience coverage than systems with fixed X° x Y° coverage patterns — projecting relatively more output to the rear of the audience, while having wide horizontal coverage close-up. Its innovative CDD driver achieves 'point source' summation of the LF and HF sections — eliminating off-axis variations in frequency response associated with non-coaxial designs. Improving on conventional coaxial designs, which can suffer from high-frequency beaming, the driver features a static waveguide that merges seamlessly with the unique cone shape — maintaining the dispersion pattern out to very high frequencies.

The visually-distinctive birch plywood enclosure can be used in either horizontal (landscape) or vertical (portrait) orientation, with rotation of the driver easily accomplished by removing the screw-free, protective grille. The CDD15 can be suspended by eyebolts or by means of an optional horizontal yoke.

Finished in black (RAL9005) or white (RAL9016) as standard, the CDD15 can be supplied in any RAL colour to order.

A full-range, passive two-way system, the CDD15 should be used with a compatible controller with appropriate limiter settings to provide system protection.

When used with the DX4.0 controller or an iKON amplifier, there are now enhanced DSP and FIR based pre-sets to deliver the absolute maximum performance and fidelity while limiter settings protect the integrity of the system.

TYPE High-output, Coaxial Differential Dispersion passive two-way system

FREQUENCY RESPONSE (5) 55Hz-18kHz ± 3dB, -10dB @ 45Hz

DRIVER LF: 15" (380mm)/3" (75mm) voice coil, long excursion, shared ferrite motor system with HF

HF: 1.4" (36mm) exit/3" (75mm) voice coil, titanium dome compression driver

RATED POWER (2) 400W AES, 1600W peak

### MARTIN AUDIO CDD15B Zvučnik

#### Features

High-output, CDD™ passive two-way system  
Coaxial Differential Dispersion™ technology  
Elegant birch plywood enclosure  
User-rotatable coaxial drive unit  
Vertical and horizontal mounting options  
Screw-free perforated steel grille  
8Ω nominal impedance  
Integral inserts for eyebolt suspension

SENSITIVITY (8) 100dB  
MAXIMUM SPL (9) 126dB continuous, 132dB peak  
NOMINAL IMPEDANCE 8Ω  
DISPERSION (-6DB) 100°-60° horizontal, 60° vertical (user-rotatable)  
CROSSOVER 1.6kHz passive  
ENCLOSURE 68 litre, birch plywood  
FINISH Black or white textured paint  
PROTECTIVE GRILLE Black or white perforated steel with scrim cloth backing  
CONNECTORS Low profile 20A push-lock  
PIN CONNECTIONS Left to right: Input+, Input -, Link -, Link+  
FITTINGS 10 x M8 fly points  
DIMENSIONS (W) 432mm x (H) 685mm x (D) 413mm  
(W) 17.01ins x (H) 26.97ins x (D) 16.26ins  
WEIGHT 26kg (57.32lbs)