

CHORD TTOBY Silver Pojačalo Snage

Šifra: 15052
Kategorija proizvoda: Pojačala Snage
Proizvođač: Chord Electronics

Cena: 419.880,00 rsd



The
TToby
range
may
be

ideally suite n't let
that fool you. with similar legendary amplification derived
from Chord's SPM range, TToby doesn't compromise on power or providing you with the purest audio
experience possible.

The TToby has been designed to complement Chord's desktop DAC/headphone amplifier, the Hugo TT and shares the same compact form factor as its stablemate. The combination of Hugo TT and TToby provides a high-quality hi-fi system, with desktop dimensions and a space-saving footprint. Despite its size, the TToby sets new standards for small amplifiers and takes full advantage of Chord Electronics' proprietary amplification technology and design know-how.

The addition of TToby, enables owners of the Hugo TT to fully exploit the device as a 'digital preamp', effortlessly driving a wide variety of loudspeakers, large or small, in addition to the Hugo TT's headphone prowess. The TToby is a 100-watt design, featuring both an unbalanced and balanced input, to take advantage of the Hugo TT's XLR output.

TToby features two of Chord's famous high-frequency power supplies and benefits from forced air-cooling through the aluminium casework by means of a sonically closed anechoic miniature multi-speed quadruple-fan plenum chamber, enabling the external design to be free of sharp heatsinks and, therefore, carry a stunning aesthetic. The Hugo TT/TToby combination offers both class-leading DAC and amplification technology via headphones and loudspeakers, giving complete flexibility within the demands of busy households.

100w into 4Ω
>-83dB Signal to Noise Ratio
Class AB Sliding Bias
HF Switch Mode Power Supply
Chord MOSFET Construction
Fully Balanced Circuitry
Fan Cooled
Stereo Balanced XLR Inputs
Stereo Unbalanced RCA Inputs
Solid Aluminium Chassis

Output Power	100w RMS per channel @ 0.016% distortion into 4Ω
Frequency Range	5Hz - 100kHz +/- 0.5dB
Signal to Noise Ratio	Better than -83dB
Channel Separation	Better than 95dB
Input Impedance	100kΩ Unbalanced/Balanced
Input Capacitance	<32pf
Output Inductance	2.6μH
Slew Rate	70v per μS 1kHz, 20v Square Wave
Gain	30dB
Stability	Unconditional
Dimensions (H x W x D) in mm	59 x 235 x 256
Weight	3.75kg