

## Pioneer XPRS10 - Aktivni zvučnik

Šifra: 15185

Kategorija proizvoda: Aktivne Zvučne Kutije

Proizvođač: Pioneer DJ

Cena: **143.880,00** rsd

The XPRS10 single PA speaker combines a 10-inch ferrite LF driver, a 1.75-inch titanium diaphragm compression driver and Pioneer Pro Audio's AFAST technology to deliver crystal clear audio with a deep bass range. Being compact, plug-and-play and easy to transport, this speaker is a reliable partner on the road, for any venue.

Natural, full-range sound

The 15-mm birch plywood cabinet, 10-inch ferrite LF driver and 1.75-inch titanium diaphragm compression driver reproduce a clean, full-range sound with low distortion, even at high outputs. Plus, the XPRS10's compact horn sounds bright and clear.

Powersoft Class D amps

Powersoft's Class D amp modules produce 2400 W (peak) or 1200 W (continuous) output. The Power Factor Correction (PFC) reduces power consumption while ensuring steady performance in all environments.

AFAST acoustic tube

Pioneer Pro Audio's AFAST technology drastically reduces standing waves that can produce a muffled response in the low to mid ranges. An acoustic tube in the cabinet absorbs only the standing waves, increasing the low-to-mid frequency response.

4 EQ modes

Adapt to a variety of genres and environments using the rotary selector switch on the back of the speaker to give you instant access to 4 EQ modes: Flat, Bass +, Speech and Wedge.

Advanced protection

The XPRS speaker is packed with features to protect the drivers, amp and power supply in to Amplifier module - giving you peace of mind, consistent high-quality sound, and extending the life of your sound system.

Flexible connectivity

2 balanced XLR/TRS combo sockets and an unbalanced RCA connection mean you can connect at the same time a Mic and other devices, such as line-level mixers or portable audio players.

Designed for the road

The durable, birch plywood enclosure keeps your PA speaker safe, while carefully placed handles take the

hard work out of transit and set-up.

Auto-ranging power supply

Plug in the XPRS Series anywhere in the world – including venues with generators or temporary power supplies. They will detect and adapt to the voltage without compromising the sound quality.

## Specifications

### Main Features

<b>What's in the box</b>	XPRS 10 x 1 Powerd cord Installation and Operation Manual Important Safety Precautions
--------------------------	--

### Specifications

<b>Width</b>	320 mm
<b>Height</b>	520 mm
<b>Depth</b>	374 mm
<b>Weight</b>	18.9 kg
<b>Frequency Range</b>	55 - 20000 Hz

## System characteristic

<b>Maximum Sound Pressure</b>	134 dB
<b>Cross Over Frequency</b>	2 kHz

## Terminals

<b>Inputs</b>	2 XLR/TRS Combo (balanced) 2 RCA (unbalanced)
<b>Outputs</b>	2 Through output XLR (balanced) 1x Mixed output XLR (balanced)

## Amplifier

<b>Amplifier Output</b>	Class D 2400W peak / 1200W cont. (LF800W / HF400W)
<b>Impedance</b>	10 k $\Omega$

## Speaker

<b>Driver</b>	10 inch ferrite LF cone driver 1.75 inch titanium diaphragm neodymium compression driver
<b>Enclosure</b>	15 mm birch plywood