

Scale Nordic SGM-TRM-0150

Šifra: 15212

Kategorija proizvoda: Linijski Kablovi

Proizvođač: Scale Technologies

Cena: **1.590,00** rsd

4-core twining process

4-core twining process (2 conductors +2 filled PVC tubes). The advantage of this is that the physical structure of a four-core process are more stable and produces less noise when the cable is moving compared to a two-core cable

Features:

High performance microphone cable

Unique, high quality, woven outer covering (6,5mm)

Hand soldered Custom male XLR connector

Hand soldered Custom 1/4-inch TRS connector with 24K gold-plated contacts

Conductor: 28 x 0.10 x 2mm (OFC)

PVC Jacket: 6 mm

Spiral shield: 84 x 0.10 (OFC)

4-core twining process: 4-core twining process (2 conductors +2 filled PVC tubes)

Included 2 cable straps

Lifetime guarantee

Available in 1.5 meter, 3 meter and 5 meter lengths

Specifications:

Cable:

Type: Custom Tweed
Microphone Cable

Color: black with blue
pattern

Overall diameter: 6.5
mm +/- 0.1 mm

Conductor area: 0.22
mm² / AWG 24

Composition of
conductor: 28 x 0.10
mm, bare annealed
copper, OFC

Conductor insulation: LD-
PE Ø 1.35 mm

Composition of cores: 4-
core twining process, 60
MM one turn, left hand

Composition of
conductor: 28 x 0,10 mm

Filler: Cotton Strand

Shield: 84 *0.10 mm,
bare annealed copper,
OFC

Jacket material:
Phthalate free PVC with
restricted substance

Working temperature:
Mobile: -5°C to +70°C,
Fixed: -20° to +70°C

Connectors:

Model name: SC013 /
SC002

Product type: XLR male /
TRS male

Number of poles: 3

Contact surface: black

Connection type: solder
contact

Colour: gold

Housing: Cast zinc

Clamping sleeve:
Polyacetal (POM)

Temperature range: -30
°C to +80 °C