

Scale Technologies SGM-TRM-0150

Šifra: 15212

Kategorija proizvoda: Linijski Kablovi

Proizvođač: Scale Technologies

Cena: **2.388,00** rsd

4-core twining process

4-core twining process (2 conductors +2 filled PVC tubes). The advantage of this is that the physical structure of a four-core process are more stable and produces less noise when the cable is moving compared to a two-core cable

Features:

- High performance microphone cable
- Unique, high quality, woven outer covering (6,5mm)
- Hand soldered Custom male XLR connector
- Hand soldered Custom 1/4-inch TRS connector with 24K gold-plated contacts
- Conductor: 28 x 0.10 x 2mm (OFC)
- PVC Jacket: 6 mm
- Spiral shield: 84 x 0.10 (OFC)
- 4-core twining process: 4-core twining process (2 conductors +2 filled PVC tubes)
- Included 2 cable straps
- Lifetime guarantee
- Available in 1.5 meter, 3 meter and 5 meter lengths

Specifications:

Cable:

- Type: Custom Tweed Microphone Cable
- Color: black with blue pattern
- Overall diameter: 6.5 mm +/- 0.1 mm
- Conductor area: 0.22 mm² / AWG 24
- Composition of conductor: 28 x 0.10 mm, bare annealed copper, OFC
- Conductor insulation: LD-PE Ø 1.35 mm
- Composition of cores: 4-core twining process, 60

MM one turn, left hand

Composition of
conductor: 28 x 0,10 mm

Filler: Cotton Strand

Shield: 84 *0.10 mm,
bare annealed copper,
OFC

Jacket material:

Phthalate free PVC with
restricted substance

Working temperature:

Mobile: -5°C to +70°C,

Fixed: -20° to +70°C

Connectors:

Model name: SC013 /
SC002

Product type: XLR male /
TRS male

Number of poles: 3

Contact surface: black

Connection type: solder
contact

Colour: gold

Housing: Cast zinc

Clamping sleeve:
Polyacetal (POM)

Temperature range: -30
°C to +80 °C