

Biamp - Apart Devio SCR-25TX Black

Šifra: 15434

Kategorija proizvoda: Konferencijski / Instalacijski

Mikrofoni

Proizvođač: Biamp - Apart



Cena: 395.760,00 rsd

Product Features

Devio SCR-25

- Works in concert with PCs running web-based conferencing solutions, including Microsoft Skype for Business/Microsoft Teams, Zoom, BlueJeans, Google Hangouts™/Google Meet, and many more
 - Supports both Windows and Mac PCs, and uses standard audio drivers
 - Supports driverless, pass-through HDMI connectivity to a single in-room display, or to two monitors with USB video using DisplayLink USB graphics technology (requires installation of DisplayLink driver on laptop; supports Windows 7, 8, 8.1, and 10)
 - Auto Setup validates device connections, adjusts room levels, and sets speaker EQ to optimise audio quality
 - Supports Bluetooth wireless technology
 - Can be monitored and managed remotely via SNMP or with the Devio System Administration Utility (SAU)
 - Firmware updates can be scheduled and deployed to multiple Devio units via the SAU
 - Speaker connectivity options include HDMI audio, a built-in 20W amplifier, or RCA line out
 - Includes a mounting bracket for under-the-table installation
 - Ships with and one tabletop or ceiling Beamtracking microphone with 360-degree coverage
 - Covered by Biamp Systems' two-year warranty
 - Parlé TTM-XEX Tabletop (Black)
 - Measures 4.7 inches (120 mm) in diameter
 - Sits directly on a tabletop to virtually disappear in room
 - Beamtracking technology actively tracks and intelligently mixes conversations
 - Four 90-degree zones for full 360-degree room coverage
 - Uses only one channel of AEC per mic
 - Single cable connection via category cable
 - Beamtracking technology works out-of-box without any lobe aiming or room mapping
 - LED mute status indicator
 - Available in either black or white
 - CE marked, UL listed, and RoHS compliant
 - Covered by Biamp Systems' two-year warranty
- #### Product Specifications
- ##### Devio SCR-25
- Network Connection: RJ-45 with Ethernet cable (Cat 5e and above)
 - Front Panel Indicators:
 - Mic Status Indicator (Green/Red LED)
 - Room Tuning Indicator (Green/Red LED)
 - Power/Wireless Indicator (Green/Red/Blue LED)
 - Power: 24V DC 60W
 - Video
 - Supported Resolutions:
 - 640 x 480p (60 Hz)

720 x 480p (60 Hz)
720 x 576p (50 Hz)
1280 x 720p (50/60 Hz)
1920 x 1080p (50/60 Hz)
3840 x 2160p (30 Hz)
Physical Interface: HDMI
HDCP Support: 1.4
HDMI Audio Formats: 2ch L-PCM, 44.1 kHz/48 kHz, 16-bit
Headset
Frequency Response (200 Hz - 8 kHz, FS): ± 0.5 dB
THD+N (1 kHz - 4 kHz, 8 kHz B/W, FS): $< 0.05\%$
Dynamic Range (THD+N $< 0.05\%$): 80 dB, A-Weighted
Maximum Output: -3 dBu
Analogue Audio Output (RCA)
Frequency Response (20 Hz - 20 kHz, FS): +0/-0.25 dB
THD+N (20 Hz - 10 kHz, 20 kHz B/W, FS): $< 0.005\%$
Dynamic Range (THD+N $< 0.005\%$): 107 dB, A-Weighted
Output Impedance (unbalanced): 100 Ω
Maximum Output: +8.5 dBu
Sampling Rate: 48 kHz
D/A Converters: 24-bit
Amplifier
Number of Channels: 1
Continuous Power Output
(THD+N $< 0.025\%$): 20 W into Rated
Load Impedance
Frequency Response
(20 Hz - 20 kHz): +0.2/-0.5 dB
THD+N (1 kHz, 20 kHz bandwidth, 1 W): $< 0.03\%$
Dynamic Range (THD+N $< 0.5\%$): 100 dB, A-Weighted
Minimum Operational Load: 4 Ω
Intermodulation distortion
(SMPTE, 60 Hz/7 kHz, 4:1, 1W): $< 0.07\%$
USB
Bit Depth: 24-bit
Sample Rate: 48 kHz
Device Charging: Up to 5 W
Bluetooth Wireless Technology
Version: 4.2, Class 2
Mode: Bluetooth Classic
Supported Profiles:
Hands-Free Profile 1.7 (HFP)
Audio/Video Remote
Control Profile 1.6 (AVRCP)
Advanced Audio
Distribution Profile 1.3 (A2DP)
Supported Codecs:
CVSD (8 kHz)
mSBC (16 kHz)
SBC (44.1 kHz)
SBC (48 kHz)
Maximum Transmit Power:
BER/EDR: 6.43 dBm (EIRP)
BLE: 7.69 dBm (EIRP)
Receive Sensitivity (0.1% BER): -88 dBm
Frequency Band: 2402-2480 MHz
Wireless Range: Up to 100 feet (30 m)
Environmental
Ambient Operating
Temperature Range: 32-104 $^{\circ}$ F (0-40 $^{\circ}$ C)
Humidity: 0-95% relative humidity (non-condensing)

Altitude: 0-6,600 ft (0-2000 m) MSL

Overall Dimensions

Height: 1.8 inches (46 mm)

Width: 11.2 inches (284 mm)

Depth: 6.9 inches (175 mm)

Weight: 2.0 lbs (0.9 kg)

Compliance

FCC Part 15B (USA)

UL and C-UL listed (USA and Canada)

CE Marked (Europe)

RoHS Directive (Europe)