



Firma: Player Plus doo  
Adresa: Svetogorska 9  
Telefon: +381 11 3347 442  
Fax: +381 11 3347 615  
PIB: 106966344  
E-mail: porudzbine@player.rs

Biamp Apart Devio SCR-25TX Black

## Biamp - Apart Devio SCR-25TX Black

Šifra: 15434

Kategorija proizvoda: Konferencijski / Instalacijski

Mikrofoni

Proizvođač: Biamp - Apart

**Cena: 395.760,00** rsd

### Product Features

Devio SCR-25

Works in concert with PCs running web-based conferencing solutions, including Microsoft Skype for Business/Microsoft Teams, Zoom, BlueJeans, Google Hangouts™/Google Meet, and many more

Supports both Windows and Mac PCs, and uses standard audio drivers

Supports driverless, pass-through HDMI connectivity to a single in-room display, or to two monitors with USB video using DisplayLink USB graphics technology (requires installation of DisplayLink driver on laptop; supports Windows 7, 8, 8.1, and 10)

Auto Setup validates device connections, adjusts room levels, and sets speaker EQ to optimise audio quality

Supports Bluetooth wireless technology

Can be monitored and managed remotely via SNMP or with the Devio System Administration Utility (SAU)

Firmware updates can be scheduled and deployed to multiple Devio units via the SAU

Speaker connectivity options include HDMI audio, a built-in 20W amplifier, or RCA line out

Includes a mounting bracket for under-the-table installation

Ships with and one tabletop or ceiling Beamtracking microphone with 360-degree coverage

Covered by Biamp Systems' two-year warranty

Parlé TTM-XEX Tabletop (Black)

Measures 4.7 inches (120 mm) in diameter

Sits directly on a tabletop to virtually disappear in room

Beamtracking technology actively tracks and intelligently mixes conversations

Four 90-degree zones for full 360-degree room coverage

Uses only one channel of AEC per mic

Single cable connection via category cable

Beamtracking technology works out-of-box without any lobe aiming or room mapping

LED mute status indicator

Available in either black or white

CE marked, UL listed, and RoHS compliant

Covered by Biamp Systems' two-year warranty

Product Specifications

Devio SCR-25

Network Connection: RJ-45 with Ethernet cable (Cat 5e and above)

Front Panel Indicators:

Mic Status Indicator (Green/Red LED)

Room Tuning Indicator (Green/Red LED)

Power/Wireless Indicator (Green/Red/Blue LED)

Power: 24V DC 60W

Video

Supported Resolutions:

640 x 480p (60 Hz)

720 x 480p (60 Hz)  
720 x 576p (50 Hz)  
1280 x 720p (50/60 Hz)  
1920 x 1080p (50/60 Hz)  
3840 x 2160p (30 Hz)  
Physical Interface: HDMI  
HDCP Support: 1.4  
HDMI Audio Formats: 2ch L-PCM, 44.1 kHz/48 kHz, 16-bit  
Headset  
Frequency Response (200 Hz - 8 kHz, FS):  $\pm 0.5$  dB  
THD+N (1 kHz - 4 kHz, 8 kHz B/W, FS):  $< 0.05\%$   
Dynamic Range (THD+N  $< 0.05\%$ ): 80 dB, A-Weighted  
Maximum Output: -3 dBu  
Analogue Audio Output (RCA)  
Frequency Response (20 Hz - 20 kHz, FS): +0/-0.25 dB  
THD+N (20 Hz - 10 kHz, 20 kHz B/W, FS):  $< 0.005\%$   
Dynamic Range (THD+N  $< 0.005\%$ ): 107 dB, A-Weighted  
Output Impedance (unbalanced): 100 $\Omega$   
Maximum Output: +8.5 dBu  
Sampling Rate: 48 kHz  
D/A Converters: 24-bit  
Amplifier  
Number of Channels: 1  
Continuous Power Output  
(THD+N  $< 0.025\%$ ): 20 W into Rated  
Load Impedance  
Frequency Response  
(20 Hz - 20 kHz): +0.2/-0.5 dB  
THD+N (1 kHz, 20 kHz bandwidth, 1 W):  $< 0.03\%$   
Dynamic Range (THD+N  $< 0.5\%$ ): 100 dB, A-Weighted  
Minimum Operational Load: 4 $\Omega$   
Intermodulation distortion  
(SMPTE, 60 Hz/7 kHz, 4:1, 1W):  $< 0.07\%$   
USB  
Bit Depth: 24-bit  
Sample Rate: 48 kHz  
Device Charging: Up to 5 W  
Bluetooth Wireless Technology  
Version: 4.2, Class 2  
Mode: Bluetooth Classic  
Supported Profiles:  
Hands-Free Profile 1.7 (HFP)  
Audio/Video Remote  
Control Profile 1.6 (AVRCP)  
Advanced Audio  
Distribution Profile 1.3 (A2DP)  
Supported Codecs:  
CVSD (8 kHz)  
mSBC (16 kHz)  
SBC (44.1 kHz)  
SBC (48 kHz)  
Maximum Transmit Power:  
BER/EDR: 6.43 dBm (EIRP)  
BLE: 7.69 dBm (EIRP)  
Receive Sensitivity (0.1% BER): -88 dBm  
Frequency Band: 2402-2480 MHz  
Wireless Range: Up to 100 feet (30 m)  
Environmental  
Ambient Operating  
Temperature Range: 32-104 $^{\circ}$  F (0-40 $^{\circ}$  C)  
Humidity: 0-95% relative humidity (non-condensing)

Altitude: 0-6,600 ft (0-2000 m) MSL

#### Overall Dimensions

Height: 1.8 inches (46 mm)

Width: 11.2 inches (284 mm)

Depth: 6.9 inches (175 mm)

Weight: 2.0 lbs (0.9 kg)

#### Compliance

FCC Part 15B (USA)

UL and C-UL listed (USA and Canada)

CE Marked (Europe)

RoHS Directive (Europe)