

Biamp - Apart CM60DTD - Plafonski zvučnik

Šifra: 15456
Kategorija proizvoda: Plafonski Zvučnici
Proizvođač: Biamp - Apart

Cena: **20.400,00** rsd

FEATURES

Requires only 6.2" (157 mm) mounting depth
High speech intelligibility coupled with full-range music reproduction
Thin-edge, magnetically attached grille
Tap switch allows for 70V/100V or 16Ω low impedance operation
Tuned bass reflex port for optimized low frequency performance
Loudspeaker overload protection for 24/7 failsafe operation
ETL listed to conform with UL Std 1480A and UL 2043;
Certified to CSA C22.2#62368-1

TECHNICAL SPECIFICATIONS

Operating Mode - Passive

Operating Environment - Indoor

Operating Range - (-10dB)75 Hz to 22 kHz

Nominal Beamwidth - (H x V)150° conical

Transducers - LF 1 x 6.5" (165 mm) coated paper cone, HF 1 x 1" (25 mm) soft dome

Continuous Power Handling@ Nominal **Impedance** - 31V60W @ 16Ω (240W peak)

Nominal Sensitivity @ 1m - @ 1W86 dB@ 2.83V83 dB

Nominal Maximum SPL @ 1m - Peak110 dBContinuous104 dB

Transformer - 70V: 60W, 30W, 15W, 7.5W, 3.75W100V: 60W, 30W, 15W, 7.5W

Protection - 3-step self-resetting protection

Recommended Amplifiers - 60W - 120W @ 16Ω (31V - 44V)

PHYSICAL

Input Connection - (1) 4-way Euroblock connector with permanent pass-through

Mounting Provisions - 2 mounting clamps with grip range of 0.2" - 2.6" (3 - 65 mm); Cover plate with 0.75" (22 mm) NPT knockout for conduit connectors

Safety Features - 2 hang points

Compliance - ETL listed to comply with UL 1480A and UL 2043; Certified to CSA C22.2#62368-1; Suitable for use in air handling spaces per NFPA 70, NFPA 90

Dimensions H x Dia. - 6.2" x 10.2" (157 mm x 258 mm)

Cutout Diameter - 9.1" (232 mm) **Weight** 8.8 lbs (4.0 kg)

Finish - Refer to the Technical Drawings (page 3)

Accessories (included) - Tile rails; tile rail spacers; cutout template

OPTIONS

Accessories - SQGR square grille