

ZOOM G6 - Procesor za gitaru

ZOOM G6 - Procesor za gitaru

Šifra: 15663

Kategorija proizvoda: Procesori

Proizvođač: ZOOM

Cena: 38.280,00 rsd

Handy iOS app. You can download new effects, amp and cabinet emulators, as well as exclusive patches from a diverse and growing list of pro guitarists.

With six pedal switches and a built-in expression pedal, the G6 lets you fly around your effects just like an analog board. There are 68 built-in rhythm parts on hand for solo performances, and you can loop over 2 hours of material when you have an SD card plugged into the board. In addition, you can expand your palette of sounds with Zoom's free Guitar Lab software for Mac and Windows, or the

Goodies Galore

240 Patches

The G6 has room for 240 patches including 100 presets, so you can build patches for each song in your repertoire and easily cycle through your setlist. Create patches of up to nine effects or seven effects plus emulation.

Integrated Pedalboard

With 6 stomp switches and an expression/volume pedal, you'll be able to change effects on the fly as you would with an analog pedalboard.

Touchscreen Functionality

The 4.3" color LCD touchscreen interface makes sound selection a breeze.

Rhythm Patterns and More

68 rhythm patterns and a built-in 2-hour looper (with SD card) let you create interesting textures all by yourself.

Built-In Audio Interface

You can use the G6 as a 2-in / 2-out interface, so you can record killer tones right to your favorite DAW.

Works with Multiple Apps

The pedal is compatible with Zoom Guitar Lab, as well as the Handy Guitar Lab iOS app. Get access to a host of killer tones, deep parameter editing, and more. Wireless control is possible via a separately available BTA-1 Bluetooth adapter.

Sounds Galore

Lots of FX

The G6 delivers the ultimate collection of Zoom's legendary guitar effects and tones, including brand new Distortion and Modulation effects. New distortion effects include Wave Shaper and Razor Drive. Polyshift is on hand for two-octave modulation, as is a doubling effect called Geminis. Chain up to 9 effects, or 7 effects with amp emulation.

Amps

The G6 provides a total of 22 cabinet emulations of all modeling amps. Plenty of classic amplifier sounds are included, and you can use them with or without included IR cab responses.

Cabs

The G6 provides 70 preloaded, full-spectrum impulse responses of cabinets, which is quite useful if you're routing your sound directly into a house PA. These impulse responses were captured by placing the microphone in three different positions. Each cabinet has a recording where the mic was placed 1" away, 12" away, and deeper out into the room.

FX

Chain up to 9 effects or 7 effects + amp emulation

4 Play Modes

Looper

Use the Looper to add layers to your sound. Create loops up to 2 hours using an SD/SDXC card.

Memory

Ideal for organizing your patches for performances, the Memory Mode allows the foot switches to activate one of the 4 patches in each bank.

Bank/Patch

This mode lets you scroll up and down through your banks and patches by clicking the corresponding foot switch.

Effect Board

This mode provides a visual representation of your pedal chain. By clicking the assigned foot switch, you can turn on or turn off an effect in your patch.

Zoom G6 Specs

Patch Memory	240 User Patches
Sampling Frequency	44.1 kHz
A/D Conversion	24-Bit with 128x Oversampling
D/A Conversion	24-Bit with 128x Oversampling
Signal Processing	32-Bit
Frequency Response	20 Hz to 20 kHz (± 0.5 dB, 10-Kilohm Load)
Display	4.3" TFT Color LCD (480 × 272)
Input	1/4" Phone Jack Rated Input Level: -20 dBu Input Impedance: 550 Kilohms
Return	1/4" Phone Jack Rated Input Level: -20 dBu Input Impedance: 1 Megohm
Aux Input	Stereo Mini Jack: 3.5 mm Rated Input Level: -10 dBu Input Impedance (Line): 10 Kilohms
Output	Output R Standard 1/4" Phone Jack Maximum Output Level: +11.4 dBu (Output Impedance 10 Kilohms or Higher) Output L/Mono (Phones) Standard 1/4" Phone Jack Maximum Output Level: +11.4 dBu (Output Impedance 10 Kilohms or Higher)
Send	Standard Stereo Phone Jack Maximum Output Level: +11.4 dBu (when Output Impedance 10 Kilohms or Higher)
Headphone	24 mW + 24 mW (at 32-Ohm Load)
S/N Ratio	123 dB
Noise Floor	Left and Right: -99.3 dBu Send: -99.0 dBu
Control Input	FP02M Expression Pedal Input
Power Adapter	AC Adapter: 9 VDC (Center Minus Plug), 500 mA (ZOOM AD-16)
USB	Port: USB 2.0 Micro-B Guitar Lab: USB 1.1 Full Speed Audio Interface: USB 2.0 Full Speed, 44.1 kHz / 32-Bit, 2-In, 2-Out

SD Card	Standards: Cards Supporting SD/SDHC/SDXC Specifications (Class 10 or Higher) Looper: 44.1 kHz / 16-Bit Stereo WAV IR: 44.1 to 192 kHz, 16- / 24- / 32-Bit WAV
Dimensions	9 x 16.5 x 2.6" / 22.8 x 41.8 x 6.5 cm
Weight	4.3 lb / 1.9 kg

Packaging Info

Package Weight	6.745 lb
Box Dimensions (LxWxH)	21.4 x 12.8 x 3.7"