

## Eightensound 12W700 8ohm - Zvučnik

---

Šifra: 15895

Kategorija proizvoda: 12 Inča

Proizvođač: Eightensound

**Cena: 27.480,00 rsd**



### Features

- 98 dB SPL 1W / 1m average sensitivity
- 75 mm (3 in) Interleaved Sandwich Voice coil (ISV)
- 450 W AES power handling
- Excellent transient response
- Weather protected cone and plates for outdoor usage
- Improved heat dissipation via unique basket design
- Ideal for compact two way, multiway systems and subwoofer applications

### Specifications

#### GENERAL SPECIFICATIONS

- Nominal Diameter: 300 mm (12 in)
- Rated Impedance: 8 Ohm
- AES Power: 450 W
- Program Power: 700 W
- Peak Power: 1500 W
- Sensitivity: 98 dB
- Frequency Range: 55 ÷ 4200 Hz
- Power Compression @-10dB: 0,8 dB
- Power Compression @-3dB: 2,3 dB
- Power Compression@Full Power: 3,1 dB
- Max Recomm. Frequency: 1700 Hz
- Recomm. Enclosure Volume: 40 ÷ 90 lt. (1,41 ÷ 3,18 cuft)
- Minimum Impedance: 7 Ohm at 25°C
- Max Peak To Peak Excursion: 34 mm (1,34 in)
- Voice Coil Diameter: 75 mm (3 in)
- Voice Coil Winding Material: aluminum
- Suspension: Triple Roll, Polycotton
- Cone: Ribbed Curvilinear, Paper

## THIELE SMALL PARAMETERS

Fs:58 Hz  
Re:5,7 Ohm  
Sd:0,0531 sq.mt. (82,31 sq.in.)  
Qms:3,93  
Qes:0,37  
Qts:0,36  
Vas:55 lt. (1,94 cuft)  
Mms:51 gr. (0,11 lb)  
BL:17,7 Tm  
Linear Mathematical Xmax:± 6,5 mm (± 0,26 in)  
Le (1kHz):1,48 mH  
Ref. Efficiency 1W@1m (half space):97,2 dB

## MOUNTING INFORMATION

Overall diameter:315 mm (12,4 in)  
N. of mounting holes:8  
Mounting holes diameter:7,15 mm (0,28 in)  
Bolt circle diameter:296 - 300 mm (11,65 - 11,8 in)  
Front mount baffle cutout ø:282 mm (11,1 in)  
Rear mount baffle cutout ø:282 mm (11,1 in)  
Total depth:147,5 mm (5,80 in)  
Flange and gasket thickness:16,5 mm (0,65 in)  
Net weight:8,2 kg (18,1 lb)  
Shipping weight:9 kg (19,87 lb)  
CardBoard Packaging dimensions:332 x 332 x 184 mm  
(13,07 x 13,07 x 7,24 in)