

## FOCUSRITE Clarett+ 2Pre

Šifra: 16011

Kategorija proizvoda: USB Zvučne kartice

Proizvođač: Focusrite  
 Display

**Cena: 38.160,00 rsd**

Channels of I/O

Tak

Noi

An

2 Ir

**Digital**

8 Inputs / 0 Outputs



Max Sample Rate/Resolution

192 kHz / 24-Bit

Number of Mic Preamps

2

Input Level Adjustment

**2 x Knob**

Expansion Slots

*None*

Pad

*None*

Gain/Trim Range

**Mic/Line/Hi-Z Inputs:**  
 +57 dB

High-Pass Filter

*None*

Solo/Mute

*None*

### Connectivity

Analog Audio I/O

**2 x** Combo XLR-1/4" TRS Balanced/Unbalanced Mic/Line/Hi-Z Input (Front Panel)  
**4 x** 1/4" TRS Balanced Line/Monitor Output  
**1 x** 1/4" TRS Unbalanced Headphone Output (Front Panel)

Phantom Power	48 V, Selectable On/Off (Selectable on Individual Inputs)
Digital Audio I/O	1 x TOSLINK Optical ADAT Input (S/MUX Support)
Host Connection / USB	1 x USB Type-C (USB 2.0)
USB (Non-Host)	None
Sync I/O	None
Network I/O	None
MIDI I/O	1 x DIN 5-Pin Input 1 x DIN 5-Pin Output
Wireless Connectivity	None

## Performance

Frequency Response	<p><b>Mic Inputs:</b> 20 Hz to 20 kHz <math>\pm 0.03</math> dB 20 Hz to 35 kHz <math>\pm 0.15</math> dB</p> <p><b>Line Inputs:</b> 20 Hz to 20 kHz <math>\pm 0.05</math> dB 20 Hz to 35 kHz <math>\pm 0.15</math> dB</p> <p><b>Hi-Z Inputs:</b> 20 Hz to 20 kHz <math>\pm 0.04</math> dB 20 Hz to 35 kHz <math>\pm 0.15</math> dB</p> <p><b>Line, Monitor Outputs:</b> 20 Hz to 20 kHz <math>\pm 0.02</math> dB 20 Hz to 35 kHz <math>\pm 0.02</math> dB</p> <p><b>Headphone Outputs:</b> 20 Hz to 20 kHz <math>\pm 0.06</math> dB 20 Hz to 35 kHz <math>\pm 0.07</math> dB</p>
Max Input Level	<p><b>Mic Inputs:</b> +18 dBu</p> <p><b>Line Inputs:</b> +26 dBu</p> <p><b>Hi-Z Inputs:</b> +15 dBu</p>
Max Output Level	<p><b>Line/Monitor Outputs:</b> +18 dBu</p> <p><b>Headphone Outputs:</b> +16 dBu</p>
Impedance	<p><b>Inputs:</b> 2.2 Kiloohms</p>

Dynamic Range	<b>Mic Inputs:</b> 118 dB (Min Gain) <b>Line Inputs:</b> 118 dB (Min Gain) <b>Hi-Z Inputs:</b> 116 dB <b>Line/Monitor Outputs:</b> 124 dB <b>Headphone Outputs:</b> > 118 dB
THD+N	<b>Mic Inputs:</b> -110 dB (+20 dB Input, at -1 dBFS) <b>Line Inputs:</b> -100 dB (Min Gain, at -1 dBFS) <b>Hi-Z Inputs:</b> -96.5 dB (Min Gain, at -1 dBFS) <b>Line/Monitor Outputs:</b> -106 dB <b>Headphone Outputs:</b> -104 dB
EIN	<b>Mic Inputs:</b> < -129 dBu

## Digital Audio

Sample Rates	44.1 / 48 / 88.2 / 96 / 176.4 / 192 kHz
Sample Rate Conversion	<i>None</i>
Bit Depths	24-Bit (AD/DA Conversion)
Sync Sources	ADAT, Internal, S/PDIF
Memory Card Slot	<i>None</i>

## Compatibility

OS Compatibility	macOS 10.11 or Later macOS 11 Windows 7 or Later
------------------	--

Included Software	<i>None</i>
Compatible Software (Not Included)	Any Core Audio (Mac) Compliant Software
Included Plug-Ins	<b>Preamp &amp; Channel Strip:</b> Brainworx bx_console Focusrite SC <b>Dynamics:</b> Focusrite Red 3 Compressor <b>Equalization:</b> Focusrite Red 2 Equalizer
Supported Drivers/API & Plug-Ins	Proprietary
Mobile Device Compatibility	<i>None</i>
Required Hardware	Available USB 2.0 Port, USB 3.0 / 3.1 Gen 1 Port, or USB Type-C Port USB Cable (Included)
Internet Connection	Required for Registration, Software/Driver Download

## Power

Power Requirements	AC/DC Power Adapter (Included) or USB Bus Power
AC/DC Power Adapter	12 VDC at 1.5 A, Center-Positive (Included)

## Physical

Anti-Theft Features	Kensington Security Slot
Dimensions	8.27 x 6.34 x 2.17" / 21.01 x 16.1 x 5.51 cm
Weight	3.0 lb / 1.4 kg

## Packaging Info

Package Weight	4.085 lb
Box Dimensions (LxWxH)	10.6 x 10.2 x 4.5"