

Firma: Player Plus doo Adresa: Svetogorska 9 Telefon: +381 11 3347 442 Fax: +381 11 3347 615

PIB: 106966344

E-mail: porudzbine@player.rs

Heil Sound PR30BK - Studijski mikrofon

Šifra: 16133

Kategorija prozivoda: Sa Velikom Dijafragmom

Proizvođač: Heil Sound

Cena: 29.880,00 rsd



microphone's supercardioid pickup pattern rejects off-axis noise, focusing on the sounds in front of it. The steel body and internal hum bucking coil shield the microphone, making it safe for use near video monitors and noisy lighting fixtures. An internal Sorbothane shock mount decouples the microphone's dynamic element from the body to reduce the effects of handling noise.

The PR 30B microphone has a hum bucking coil, in addition to the large shock-mounted diaphragm. Electronic noises will not affect your mix when using the PR 30B near PC monitors in the studio, nor near neon lights and vibration is not an issue with the PR 30B. The PR 30B can handle 146 dB of SPL.

Ribbon-Like Sound

The large dynamic element has a smooth frequency response with a natural and articulate midrange, providing a ribbon-like sound

Wide Dynamic Range

The large size and low mass of the microphone element, combined with a powerful NdFeB magnet structure, give the microphone a cardioid pattern with exceptional off-axis rejection, and the ability to capture high SPLs while providing a wide dynamic range
Specialized Screen System
The microphone's screen system uses two different mesh screens and an internal filter to keep sibilance and plosives to a minimum
Internal Shock Mount
The internal Sorbothane mount decouples the microphone element from the body, reducing the effects of handling noise
Heavily Shielded
The rugged steel body and internal hum bucking coil shield the microphone, allowing you to use it near video monitors and noisy light fixtures
Assembled in the USA
The PR 30B is assembled and tested in Illinois

Heil Sound PR 30 Specs

Microphone

Form Factor	Stand/Boom Mount
Sound Field	Mono
Capsule	Dynamic
Diaphragm	1.5" / 38.10 mm
Polar Pattern	Cardioid
Orientation	End Address
High-Pass Filter	Yes
Gain Adjustment	Yes
Windscreen	None

Performance

Frequency Range	40 Hz to 18 kHz
Maximum SPL	146 dB SPL
Impedance	370 Ohms
Sensitivity	-51 dB at 1 kHz
Output Level	51 dB

Connectivity

Output Connectors (Analog)		1 x XLR 3-Pin		
Dhysical				
Physical				
Color	Black			
Mounting	Mic Clip/Stand	Mic Clip/Stand Adapter		
Included Case	Zipper Pouch	Zipper Pouch		
Included Filters	None	None		
Weight	9 oz / 255.15 g			
Packaging Info				
Package Weight		1.29 lb		
Box Dimensions (LxWxH)		9.95 x 5.4 x 2.8"		