

## audiolab 6000CDT CD Transport Aluminium Blk

audiolab 6000CDT CD Transport Aluminium Blk

Šifra: 16404  
Kategorija proizvoda: CD Plejeri  
Proizvođač: Audiolab

Cena: **47.880,00** rsd

With an output impedance of 75 ohms, the CD Transport device ensures a healthy power transmission system. The 6000CDT features a 12V trigger output and auto standby mode to avoid excess heating and power consumption. With a maximum power consumption of 20W and standby power consumption of less than 0.5W, it is an energy efficient device. The 6000CDT with dimensions 445(W) x 300(H) x 65.5(D) mm weighs only 7.2 kg. The CD transport comes with a remote control to help you operate the system even from a distance. Kick back on your comfy couch and play the 6000CDT with your favourite genre of music. The CD transport system is available in black or silver finishes to add a stylish look to your living room and interiors.

|                              |   |
|------------------------------|---|
| Digital Output Voltage Level | 600±50mVpp  |
| Frequency response           | ≤0.01dB @ 20-20kHz [-] ≤0.01dB @ 20-20kHz                             |
| Output Impedance             | 75±1 ohm  |
| Max Sampling Rate            | 44.1 KHz  |
| Max. Power Consumption       | 15W   |
| Standby Power Consumption    | <0.5W   |
| Power Requirements           | 240V ~ 50 - 60Hz  |
|                              | 230V ~ 50 - 60Hz  |
|                              | 115V ~ 50 - 60Hz  |
|                              | 100V ~ 50 - 60Hz  |
| Dimensions (mm)              | (W x H x D) 445 x 300 x 65.5 - including feet, terminals and controls |
| Carton Size (mm)             | (W x H x D) 512 x 467 x 146   |
| Weight (kg)                  | 5.4   |