

audiolab 6000CDT CD Transport Aluminium Slv

Šifra: 16396
Kategorija proizvoda: CD Plejeri
Proizvođač: Audiolab

Cena: 52.680,00 rsd



With
an

output impedance of 75 ohms, the CD Transport device ensures a healthy power transmission system. The 6000CDT features a 12V trigger output and auto standby mode to avoid excess heating and power consumption. With a maximum power consumption of 20W and standby power consumption of less than 0.5W, it is an energy efficient device. The 6000CDT with dimensions 445(W) x 300(H) x 65.5(D) mm weighs only 7.2 kg. The CD transport comes with a remote control to help you operate the system even from a distance. Kick back on your comfy couch and play the 6000CDT with your favourite genre of music. The CD transport system is available in black or silver finishes to add a stylish look to your living room and interiors.

Digital Output Voltage Level $600 \pm 50 \text{mVpp}$

Frequency response $\leq 0.01 \text{dB @ } 20\text{-}20 \text{kHz [-]} \leq 0.01 \text{dB @ } 20\text{-}20 \text{kHz}$

Output Impedance $75 \pm 1 \text{ ohm}$

Max Sampling Rate 44.1 KHz

Max. Power Consumption 15W

Standby Power Consumption $< 0.5 \text{W}$

Power Requirements 240V ~ 50 - 60Hz

230V ~ 50 - 60Hz

115V ~ 50 - 60Hz

100V ~ 50 - 60Hz

Dimensions (mm) (W x H x D) 445 x 300 x 65.5 - including feet, terminals and controls

Carton Size (mm) (W x H x D) 512 x 467 x 146

Weight (kg) 5.4