

## audiolab 6000CDT CD Transport Aluminium Slv

---

Šifra: 16396  
Kategorija proizvoda: CD Plejeri  
Proizvođač: Audiolab

Cena: **47.880,00** rsd

With an output impedance of 75 ohms, the CD Transport device ensures a healthy power transmission system. The 6000CDT features a 12V trigger output and auto standby mode to avoid excess heating and power consumption. With a maximum power consumption of 20W and standby power consumption of less than 0.5W, it is an energy efficient device. The 6000CDT with dimensions 445(W) x 300(H) x 65.5(D) mm weighs only 7.2 kg. The CD transport comes with a remote control to help you operate the system even from a distance. Kick back on your comfy couch and play the 6000CDT with your favourite genre of music. The CD transport system is available in black or silver finishes to add a stylish look to your living room and interiors.

Digital Output Voltage Level      600±50mVpp

Frequency response      ≤0.01dB @ 20-20kHz [-] ≤0.01dB @ 20-20kHz

Output Impedance      75±1 ohm

Max Sampling Rate      44.1 KHz

Max. Power Consumption      15W

Standby Power Consumption      <0.5W

Power Requirements      240V ~ 50 - 60Hz

230V ~ 50 - 60Hz

115V ~ 50 - 60Hz

100V ~ 50 - 60Hz

Dimensions (mm) (W x H x D) 445 x 300 x 65.5 - including feet, terminals and controls

Carton Size (mm) (W x H x D) 512 x 467 x 146

Weight (kg) 5.4