

## Vertere Magneto MM Gramofonska Glava

---

Šifra: 16422

Kategorija proizvoda: Igle i Glave

Proizvođač: Vertere

Cena: **23.880,00** rsd

### Magneto

A high-specification Dual Moving Magnet Phono Cartridge, Magneto has been designed and manufactured by Vertere Acoustics to their exacting standards, and delivers an unparalleled musical experience in its class.

An ideal starter cartridge for new phonograph owners with a love of high-fidelity, Magneto is quiet, dynamic, accurate, easy to optimise, tolerant of records in less-than-perfect condition (which is often the case when owners return to vinyl after many years of absence), yet superbly musical, imbued with all the qualities one expects of Vertere products.

The dual magnet layout replicates the structure of the cutter head, with a V-form twin-magnet design to mimic the left & right channel sides of the record groove.

Permalloy centre shield plating provides a higher frequency response, with electrical crosstalk typically better than 40dB.

Use of laminated para-toroidal coils, along with the aforementioned "V" geometry of the magnets also gives rise to higher efficiency in generating the output signal.

Magneto utilises a finely-finished elliptical stylus to ensure outstanding tracking ability, plus super-quiet tracing of the record groove.

Magneto is closely related to the Audio Technica VM520EB cartridge (originally fitted to the DG-1) and is stylus-compatible with the AT VM5x range. This allows Magneto owners to upgrade to an improved stylus profile - if desired - when the time comes to renew.

### Features

Replaceable Stylus

Integrated Stylus Guard

Stainless Steel Fixing Bolts, Washer & Hex Thumb Nuts

Easy Alignment-Assist Markings

### Specifications

Frequency Response: 20 - 23,000Hz

Channel Separation: 27dB (1kHz)

Output Channel Balance: 1.5dB (1kHz)

Output Voltage: 4.5mV (1kHz, 5cm/sec.)

Vertical Tracking Angle: 23 °

Vertical Tracking Force Range: 1.8 - 2.2g (2.0g standard)

Stylus Shape: Elliptical Bonded

Stylus Size: 0.3 x 0.7 mil  
Stylus Construction: Bonded Round Shank  
Cantilever: Aluminium Tube  
Coil Impedance: 2,700 Ohm (1kHz)  
Static Compliance: 35 x 10<sup>-6</sup> cm/dyne  
Dynamic Compliance: 8 x 10<sup>-6</sup> cm/dyne (100Hz)  
Recommended Load Impedance: 47,000 Ohm  
Recommended Load Capacitance: 100 - 200pF  
Weight: 6.4g  
Dimensions: 17.3 (H) x 17.0 (W) x 28.2 (L) mm

<b>Weight</b>	0.064 kg
<b>Dimensions</b>	2.82 x 1.7 x 1.73 cm
<b>Colour</b>	Black / White / Orange