

TASCAM SS-CDR250N

TASCAM SS-CDR250N

Šifra: 16600
Kategorija proizvoda: Snimači/Rekorderi
Proizvođač: TASCAM

Cena: **171.216,00** rsd

The SS-CDR250N is the ideal SD card recorder/players with CD recorder, having a variety of features with extensive terminal equipment applications and business applications. An FTP client function is added which enables the exchanges of sound source data with others via server communication. You can also keep the starting time accurate for recording and playback based on time management via SNTP. The remote control with the dedicated app on a iOS/Android/Windows/Mac device, and the mic inputs are also available on the unit which allows you to use in many ways with flexibility.

Network functions / control functions

FTP Client function enables automatic uploading of recorded files or downloading audio files from the server
Event List for recording, playback, download and other functions can be operated automatically based on the time set

Time setting via SNTP Client function enables event management with more accuracy

Automatic Upload function enables recorded files to be uploaded automatically

iOS / Android / Windows / Mac control apps available: allowing transport operations and remote control of various settings

The IF-DA2 interface card supporting Dante 2ch input and output can be installed (sold separately)

Serial and parallel port connections

RC-SS150 Flash Start control unit with the a color LCD screen (sold separately)

Optional RC-3F footswitch can be connected to the RC-20 remote control

Recording capabilities

Supports recording and playback of high-resolution files up to 96kHz/24-bit

Dual SD memory card slot permits mirror and relay recording

Auto mark function: When an error occurs or input level overloads, the time point will be marked automatically

PRE REC function to prevent any missing part in your recording

Auto track function automatically trims the tracks

Compressor and limiter included

Auto level control function automatically adjusts the input level for recording

Starts recording as soon as the unit is turned on with Power-on-record function

Microphone input connector with phantom power supply

Direct recording function enables the recording starts right away without any standby

Playback functions

Call function that saves the position where your last playback starts

Playback modes such as Program, Random, and Single

Ducking function automatically adjusts the playback volume while the input level increases or decreases

All repeat / A-B repeat function

Incremental play function to transport to the beginning of the next track

Monaural mix playback function

Auto Cue function tracks the first sound in the playback for standby

Auto ready function allows a standby before the next track begins
Pitch control and key control function for speed and key adjustments
Can set the mark at any position
EOM (End of message) notification available before the track ends
Other features

Sampling rate converter for inputs and outputs are available
Link playback function allows two units to be operated at the same time
Automatic file closing process to avoid data loss if there is a sudden power loss during recording
User presets: Up to three sets of optional settings can be stored for such things as switching input and output, sampling rate selection and other functions
1U rack-mount size