

WOLFMIX-W1

Šifra: 16648
Kategorija proizvoda: DMX Kontrole i Dimeri
Proizvođač: Wolfmix

Cena: **59.880,00** rsd

Robustan hardver u sebi nosi moćan procesor, sa pregršt modula efekata, mogućnosti sinhronizacije sa muzikom, i do 4 DMX Universe-a. Visoko taktilne kontrole i intuitivan proces rada učiniće manipulisanje rasvetom za **Wolfmix** kontrolerom pravim zadovoljstvom. Izaberite između hiljade svetlosnih opcija, ili napravite sopstvenu konfiguraciju sa ovim svestranim uređajem. Bilo da je u pitanju živo izvođenje, klupski/disko performans ili neka druga vrsta nastupa - **Wolfmix** je siguran izbor.

Displej od 4.3" osetljiv na dodir, 37 *backlit* silkonskih dugmića u boji, 4 kontrolna potenciometra, i dodeljiva dugmad za strob, blinder, speed, blackout & smoke. Lako selektovanje, 'pozivanje' i grupisanje preko 3500 integrisanih, predefinisanih profila. Plus, tu je još i 15000 dodatnih predpodešenih profila koji su dostupni putem podržane WTOOLS aplikacije.

The WMX1 includes a fixture builder, for creating custom profiles or for use with old or obscure fixtures. It also includes a Fixture Calibration Tool, which allows limiting the area covered by moving heads.

American DJ WMX1 Specs

Setup: Standalone (No Computer Needed)

Compatible with Any DMX Device

Standard Unit Comes With 1 DMX Universe but Up To 3 Additional Universes Are Available as Add-Ons, which Are Sold via the WTOOLS App

Up to 680 Fixtures & Beams, Up to 50 Fixture Types, Up to 5000 Fixture Features (Color/Gobo, Etc.)

8 Fixture Groups, 6 Projects, 15000+ Available Fixtures (3500+ on the Controller)

DMX Address, Fixture Order, and Group Setup

Use as a DMX Splitter with DMX Universe Mapping

FX: Color FX Module with 8 Effect Types and 16 Definable Colors

Move FX Module with 8 Effect Types, Beam FX Module with 8 Effect Types

6 Flash Buttons For Controlling Special FX, Strobe, Blinder, Speed, Blackout, and Smoke

Static Color Palette with 10 User-Definable Colors Per Group and Gradient Control

Static Position Palette with 5 User-Definable Positions Per Group with Fade and Fanning

Gobo Palette With 5 User Definable Gobos Per Group

20 Nameable Live Edit Buttons with Flash Triggering Mode and Park Function

100 Nameable Presets For Storing Snapshots with Hold and Fade Timings

Preset Playback Cue List—All Presets or Per Page of 20 Presets

Control Group and Master Dimming with Encoder Acceleration

Group Flash, Full and Blackout; 16-Bit Pan/Tilt Control

Multibeam Led Bar Control

FX Music Pulse Sync from Microphone or Line-in, FX BPM Sync with Ableton Link, OS2L, or BPM Tap

Effect Speed, Phase, Order, Size, Fade, Fan, and Flick

Live Control of Move FX Registration Point

Global FX Speed and Freeze Control

Map DMX In with Group Dimmer and Patch to Output Channels

WLINK—Sync with Another WOLFMIX Controller

Tools: Fixture Builder, Fixture Calibration Tool to Limit the Area of Moving Fixtures

X-Y Touch Controlled Positioning Grid, RGBW Touch-Controlled Color Picker,

8-Step Real-Time Sequencer for Creating Beam and Move FX,

Live View of DMX Levels with Default Value Override and DMX Channel Tester

Beam Editor to Override Min and Max Values Used in Generated FX.

Advanced Features: Calibrate and RGB, White, Amber, UV Mixing with Automatic Fixed-Color Wheel Translation

Automatic Match of Similar Gobos across Different Fixture Types

Timed Release of Flash and Preset Buttons

Fixture Flip Function, for Reversing Beam Order

Fixture Split Function, for Splitting Up Multi-FX Bars

Lock Full Controller or Lock Editing with A Password

Project and Fixture Backup with WTOOLS App

Offline 3D Visualization with Easy View and WTOOLS Over USB

Auto-Recovery of Active Project (No Manual Saving Needed)

Import Different Fixture Setups into the Same Project

Starts in Under 2 Seconds. Starts Sending DMX in Under 1 Second

Factory Firmware Startup Recovery Mode for Times of Crisis

Display: 4.3" Color TFT with Tinted Glass, Capacitive Touch

Encoders: Alloy; Incremental Push with Acceleration

Pads - 37 Silicone Button Pads with Matte Oil Finishing

LED Color Backlit

Processing: 220 MHz CPU with ARM Core, 8 MB RAM, 16 MB Flash

Audio: Omnidirectional Electret Mic

1/8" / 3.5mm Jack Line-In

Analog Adaptive Peak Detector

DMX: 2 x 3-Pin DMX Out XLR Connectors

1 x 5-Pin DMX Out XLR Connector, 1 x 5-Pin DMX In/Out XLR Connector with WLINK

Enclosure: ABS Plastic

Powder-Coated Steel Base Plate with 3.9" / 100.0 mm VESA (M4 Max: 0.2" / 6.0 mm)

Powder-Coated Steel Reinforced Back Plate

Power - USB Powered: USB Type-B, 900 mA (USB Type-3 Rating)

Dimensions: 19.5 x 22.0 x 6.2 cm, Weight: 1.1 kg