

Firma: Player Plus doo Adresa: Svetogorska 9 Telefon: +381 11 3347 442 Fax: +381 11 3347 615 PIB: 106966344 E-mail: porudzbine@player.rs

Saramonio SoundBird Min

# Saramonic SoundBird V1

Šifra: 16710 Kategorija prozivoda: Mikrofoni Za Kamere Proizvođač: Saramonic

# Cena: **32.280,00** rsd

The SoundBird V1 can be powered via a AA battery or +48V phantom power supplied from an XLR-equipped camera or recorder.

At 10.7", the SoundBird V1 is well suited for use mounted on a camera shoe, boompole, or stand (using the included shockmount). The mic comes with a protective foam windscreen and can benefit from the Saramonic TM-WS1 furry windshield (available separately) when recording in high-wind environments.

## **Optimize Your Sound in Various Situations**

A low-cut button helps eliminate unwanted low rumble coming from HVAC, footsteps, or traffic noise. A -10 dB pad allows you to capture loud sounds without clipping.

All the buttons are illuminated so you can easily see the settings, and an On/Off button changes color based on the power source and battery level. Your settings are saved when you turn the mic On and Off.

### **Other Features**

The durable solid brass construction prevents radio-frequency interference.

The gold-plated XLR connector resists corrosion to ensure a clean signal.

Includes a shockmount to attach mic to cameras or boompoles, a foam windscreen, and an XLR output cable (2').

In the Box

Saramonic SoundBird V1 Shotgun Microphone (Battery, Phantom) SR-SMC2 Adjustable Shockmount 4 x Replacement Shockmount Bands Foam Windscreen XLR Mic Cable (2') Limited 1-Year Warranty

### Saramonic SOUNDBIRDV1 Specs

Microphone Form Factor Camera-Mount Sound Field Mono Capsule 1 x Electret Condenser Polar Pattern Supercardioid Orientation End Address Pad -10 dB High-Pass Filter 200 Hz Gain Adjustment None Indicators 1 x Blue/Green/Red Single LED (Phantom Power, Power, Status) On-Board Controls High-Pass Filter, Pad Windscreen Foam (Included) Performance

Frequency Range 50 Hz to 20 kHz Maximum SPL 132 dB SPL (1 kHz, 1% THD) Sensitivity -32 dB at 1 kHz Signal-to-Noise Ratio 80 dB SPL Connectivity Output Connectors (Analog) 1 x XLR 3-Pin Female (Locking, on Mic) Power Operating Voltage 48 V (Battery Power, Phantom Power) Battery Type 1 x AA (Not Included) Physical Mounting Shockmount Included Case None **Construction Material Brass** Dimensions ø: 0.79 x L: 10.71" / ø: 2.01 x L: 27.2 cm Weight 6.88 oz / 195 g Packaging Info Package Weight 1.35 lb Box Dimensions (LxWxH) 13.3 x 6.5 x 2.65"

Cene su informativnog karaktera. Prodavac ne odgovara za tačnost cena iskazanih na sajtu, zadržava pravo izmena cena. Ponudu za ostale artikle, informacije o stanju lagera i aktuelnim cenama možete dobiti na upit. Plaćanje se isključivo vrši virmanski - bezgotovinski.