

Saramonic SoundBird V1

Šifra: 16710
Kategorija proizvoda: Mikrofoni Za Kamere
Proizvođač: Saramonic

Cena: **32.280,00** rsd

The SoundBird V1 can be powered via a AA battery or +48V phantom power supplied from an XLR-equipped camera or recorder.

At 10.7", the SoundBird V1 is well suited for use mounted on a camera shoe, boompole, or stand (using the included shockmount). The mic comes with a protective foam windscreen and can benefit from the Saramonic TM-WS1 furry windshield (available separately) when recording in high-wind environments.

Optimize Your Sound in Various Situations

A low-cut button helps eliminate unwanted low rumble coming from HVAC, footsteps, or traffic noise. A -10 dB pad allows you to capture loud sounds without clipping. All the buttons are illuminated so you can easily see the settings, and an On/Off button changes color based on the power source and battery level. Your settings are saved when you turn the mic On and Off.

Other Features

The durable solid brass construction prevents radio-frequency interference. The gold-plated XLR connector resists corrosion to ensure a clean signal. Includes a shockmount to attach mic to cameras or boompoles, a foam windscreen, and an XLR output cable (2').
In the Box

Saramonic SoundBird V1 Shotgun Microphone (Battery, Phantom)
SR-SMC2 Adjustable Shockmount
4 x Replacement Shockmount Bands
Foam Windscreen
XLR Mic Cable (2')
Limited 1-Year Warranty

Saramonic SOUNDBIRDV1 Specs

Microphone
Form Factor Camera-Mount
Sound Field Mono
Capsule 1 x Electret Condenser
Polar Pattern Supercardioid
Orientation End Address
Pad -10 dB
High-Pass Filter 200 Hz
Gain Adjustment None
Indicators 1 x Blue/Green/Red Single LED (Phantom Power, Power, Status)
On-Board Controls High-Pass Filter, Pad
Windscreen Foam (Included)
Performance

Frequency Range 50 Hz to 20 kHz

Maximum SPL 132 dB SPL (1 kHz, 1% THD)

Sensitivity -32 dB at 1 kHz

Signal-to-Noise Ratio 80 dB SPL

Connectivity

Output Connectors (Analog) 1 x XLR 3-Pin Female (Locking, on Mic)

Power

Operating Voltage 48 V (Battery Power, Phantom Power)

Battery Type 1 x AA (Not Included)

Physical

Mounting Shockmount

Included Case None

Construction Material Brass

Dimensions \varnothing : 0.79 x L: 10.71" / \varnothing : 2.01 x L: 27.2 cm

Weight 6.88 oz / 195 g

Packaging Info

Package Weight 1.35 lb

Box Dimensions (LxWxH) 13.3 x 6.5 x 2.65"