

## Saramonic SoundBird V1

Šifra: 16710  
Kategorija proizvoda: Mikrofoni Za Kamere  
Proizvođač: Saramonic

Cena: **32.280,00** rsd

The SoundBird V1 can be powered via a AA battery or +48V phantom power supplied from an XLR-equipped camera or recorder.

At 10.7", the SoundBird V1 is well suited for use mounted on a camera shoe, boompole, or stand (using the included shockmount). The mic comes with a protective foam windscreen and can benefit from the Saramonic TM-WS1 furry windshield (available separately) when recording in high-wind environments.

### Optimize Your Sound in Various Situations

A low-cut button helps eliminate unwanted low rumble coming from HVAC, footsteps, or traffic noise. A -10 dB pad allows you to capture loud sounds without clipping. All the buttons are illuminated so you can easily see the settings, and an On/Off button changes color based on the power source and battery level. Your settings are saved when you turn the mic On and Off.

### Other Features

The durable solid brass construction prevents radio-frequency interference. The gold-plated XLR connector resists corrosion to ensure a clean signal. Includes a shockmount to attach mic to cameras or boompoles, a foam windscreen, and an XLR output cable (2').  
In the Box

Saramonic SoundBird V1 Shotgun Microphone (Battery, Phantom)  
SR-SMC2 Adjustable Shockmount  
4 x Replacement Shockmount Bands  
Foam Windscreen  
XLR Mic Cable (2')  
Limited 1-Year Warranty

### Saramonic SOUNDBIRDV1 Specs

Microphone  
Form Factor Camera-Mount  
Sound Field Mono  
Capsule 1 x Electret Condenser  
Polar Pattern Supercardioid  
Orientation End Address  
Pad -10 dB  
High-Pass Filter 200 Hz  
Gain Adjustment None  
Indicators 1 x Blue/Green/Red Single LED (Phantom Power, Power, Status)  
On-Board Controls High-Pass Filter, Pad  
Windscreen Foam (Included)  
Performance

Frequency Range 50 Hz to 20 kHz

Maximum SPL 132 dB SPL (1 kHz, 1% THD)

Sensitivity -32 dB at 1 kHz

Signal-to-Noise Ratio 80 dB SPL

Connectivity

Output Connectors (Analog) 1 x XLR 3-Pin Female (Locking, on Mic)

Power

Operating Voltage 48 V (Battery Power, Phantom Power)

Battery Type 1 x AA (Not Included)

Physical

Mounting Shockmount

Included Case None

Construction Material Brass

Dimensions  $\varnothing$ : 0.79 x L: 10.71" /  $\varnothing$ : 2.01 x L: 27.2 cm

Weight 6.88 oz / 195 g

Packaging Info

Package Weight 1.35 lb

Box Dimensions (LxWxH) 13.3 x 6.5 x 2.65"