

Neutrik NP3RX

Šifra: 16755
Kategorija proizvoda: Konektori
Proizvođač: Neutrik

Cena: 800,00 rsd



precise machined it rivets makes
it unique and avoids hook up in a socket or break off the tip.

The Plug X Series serves all applications such as guitar applications, audio cables, snakes, speakers, amplifiers and mixing desks.

Features & Benefits

All metal housing eliminates the plastic cover of the predecessor NP*RCS and improves further durability and EMI protection
Extra slim 1/4" plug for highest packing density
Robust diecast shell in stylish design
Proven chuck type strain relief for reliable cable retention
Sleek design for best handling convenience
Precision machined one-piece contacts - avoid hook up of tip contact

Technical Information

Product
Title NP3RX
Connection Type Plug
Gender male
Electrical
Contact resistance depends on mating connector mΩ
Dielectric strength 1 kVdc
Insulation resistance > 2 GΩ (initial)
Rated current per contact depends on mating connector A
Rated voltage < 50 V
Mechanical
Cable O.D. 4 - 7 mm
Lifetime > 1000 mating cycles
Wiresize 1 mm²
Wiresize 18 AWG
Wiring Solder contacts
Material
Bushing Polyacetal (POM) + PU
Contact plating 2 μm Ni (Su)
Contacts Brass (CuZn39Pb3)
Insert Polyamide (PA 6.6 30 % GR)
Shell Zinc diecast (ZnAl4Cu1)
Shell plating Nickel
Strain relief Polyacetal (POM)
Environmental
Standard compliance IEC 60603-11 / EIA RS-453
Solderability Complies with IEC 68-2-20

Temperature range -20 °C to +65 °C