

Neutrik NP3RX type unknown

Neutrik NP3RX

Šifra: 16755

Kategorija proizvoda: Konektori

Proizvođač: Neutrik

Cena: **984,00** rsd

The precise machined one-piece tip contact without rivets makes it unique and avoids hook up in a socket or break off the tip.

The Plug X Series serves all applications such as guitar applications, audio cables, snakes, speakers, amplifiers and mixing desks.

Features & Benefits

All metal housing eliminates the plastic cover of the predecessor NP*RCS and improves further durability and EMI protection
Extra slim 1/4" plug for highest packing density
Robust diecast shell in stylish design
Proven chuck type strain relief for reliable cable retention
Sleek design for best handling convenience
Precision machined one-piece contacts - avoid hook up of tip contact

Technical Information

Product

Title NP3RX

Connection Type Plug

Gender male

Electrical

Contact resistance depends on mating connector mΩ

Dielectric strength 1 kVdc

Insulation resistance > 2 GΩ (initial)

Rated current per contact depends on mating connector A

Rated voltage < 50 V

Mechanical

Cable O.D. 4 - 7 mm

Lifetime > 1000 mating cycles

Wiresize 1 mm²

Wiresize 18 AWG

Wiring Solder contacts

Material

Bushing Polyacetal (POM) + PU

Contact plating 2 μm Ni (Su)

Contacts Brass (CuZn39Pb3)

Insert Polyamide (PA 6.6 30 % GR)

Shell Zinc diecast (ZnAl4Cu1)

Shell plating Nickel

Strain relief Polyacetal (POM)

Environmental

Standard compliance IEC 60603-11 / EIA RS-453

Solderability Complies with IEC 68-2-20

Temperature range -20 °C to +65 °C