

## FBT X-LITE 110A - Aktivni zvučnik

Šifra: 16800

Kategorija proizvoda: Aktivne Zvučne Kutije

Proizvođač: FBT

Cena: **49.920,00** rsd

### PRODUCT DESCRIPTION

The FBT XLITE 110A series speakers with integrated 3-channels mixer feature lightweight, yet rugged gas injected molded polypropylene cabinet construction. Available in black finish, the FBT XLITE 110A series speakers provide fixed installations with an elegant design that blends into any decor.

The asymmetrical shape of the FBT XLITE 110A cabinet also allows use as a powered floor stage monitor.

The FBT XLITE 110A is two way design incorporating a 10" low frequency woofer and 1" HF compression driver coupled to a 90°H x 60°V constant directivity horn. With a frequency range of 58Hz - 20kHz the FBT XLITE 110A speaker provide high fidelity sound for both speech and music applications with a maximum SPL of 127dB.

The bi-amplified FBT XLITE 110A active speaker feature a 1200W low frequency amp and a 300W high frequency amp. The control panel features a three-channel mixer with two micro-line inputs, a stereo input and a dedicated channel for bluetooth 5.0; two XLR inputs, stereo input, XLR output with ch1 or mix link selector, HP filter, two mic-line selectors, DSP preset selector, Bluetooth 5.0 with pairing led. 4 x M10 rigging points built-in into the cabinet along with the optional mounting brackets allow the FBT XLITE 110A speaker to be surface mounted on walls or ceilings.

A standard 35mm speaker stand socket allows the FBT XLITE 110A to be mounted on speaker stand

### KEY FEATURES

- 2 way bi-amplified bass reflex system
- Polypropylene moulded enclosure
- Custom 10" woofer (LF) / 2.5" voice coil
- 1" throat / 1.4" voice coil HF compression driver
- 1200w / 300w Built-In amplifier (LF / HF)
- Bluetooth 5.0
- 3-Channel mixer
- 4 DSP Presets
- 30 degrees & 45 degrees monitor tapers
- Universal switch mode power supply 100-240 VAC
- M10 rigging points

### SPECIFICATIONS

- Configuration: 2 Way
- Frequency response: 58Hz - 20KHz
- Low frequency woofer: 10" - 2.5" VC
- High frequency driver: 1" - 1.4" VC
- Maximum SPL cont/peak: 123/127 dB
- Dispersion: 90 x 60
- Input impedance: 22

Input connector: XLR IN/OUT

Net Dimension (WxHxD): 300 x 536 x 301.5

Net Weight: 13 KG

Transport Dimension (WxHxD): 370 x 615 x 380

Transport Weight: 14.8 KG

Built in amplifier peak: LF 1200w HF 300w