

MACKIE Onyx16 - Mikseta bez snage/Pasivna mikseta

Šifra: 16848

Kategorija proizvoda: Studijske Miksete

Proizvođač: MACKIE

Cena: 77.880,00 rsd



Onyx16 ispunjen je sjajnim sadržajima, tu su Perkins ekvilajzer u britanskom stilu, moćni DSP efekti, displej u punom koloru, kao i integrisano stereo snimanje i plejbek sa SD kartice. Mikser nudi end-to-end performanse ultra niskog šuma, koje zahteva rad studijskih profesionalaca.

Klasičan zvuk, moderne performanse

Višestruko nagrađivana Onyx prepojačala donose do 60 dB jačine.

Premijum analogna kola isporučuju studijski kvalitet zvuka i šum drže na minimumu.

Direktno stereo (2x2) snimanje i plejbek na SD karticu

Višekanalno (24x4) snimanje u visokoj rezoluciji (96 kHz / 24-bit), za Mac/PC via USB

Direktno na SD kartu (2x2) stereo snimanje i plejbek

Četvorokanalni, dodeljivi USB return (2 stereo para)

Pošaljite vaš Main Mix na USB jednostavno, putem prekidača

Displej u punom koloru za sve studio komande, plus interfejs kontrolisan jednim potencijetrom

Jednostavna navigacija parametara efekata, onboard SD snimanje i plejbek

Vizualno pregledajte fajlove na SD kartici putem ugrađenog displeja

Dodeljivi (fizički) dugmići za komande: Previous, Next, Record, Play/Pause

Sačuvajte do 6 korisničkih presetova efekata za brz i lak odziv

Profesionalni procesor efekata visoke rezolucije

Korišćenje integrisanih efekata za lajv performanse, strimovanje i drugo.

Reverb, Delay, Chorus, itd.

Postignite savršen zvuk uz podesive parametre i dodeljive ekvilajzere

Bluetooth Streaming for Wireless Audio Streaming

Pair your Bluetooth enabled device and stream audio directly to a channel on the mixer
Streamed audio can be routed to Aux Sends and the Main Mix

Powerful Mixing Toolkit

3-band Perkins EQ with on/off hard-bypass switch on all channels
Hi-Z switches allows direct connection of guitars, basses, and other instruments
100 Hz low-cut filter and 48V phantom power on all mic channels
Stereo 3.5mm input and Bluetooth streaming
Stereo line inputs
Aux/Monitor outputs with dedicated per-channel send control
Dedicated Control Room outputs
Headphone output with dedicated level control
L/R Assign switch per channel
12-segment stereo meters
Overload indicators on all channels
PFL/AFL channel solo
Footswitch input for FX Mute (footswitch not included)
Powerful Software and Plugins
Waveform OEM recording software and plugin bundle
DAW Essentials Bundle for Waveform OEM, with 16 powerful plugins like Equalizer, Compressor, Reverber8, and Limiter
Rugged Chassis and Professional Design
Backlit mute and solo buttons provide a positive tactile feel and clear visual feedback

Mackie ONYX16 Specs

Mixer
Number of Analog Input Channels: 18 (8 Mono / 5 Stereo)
Number of Mic Preamps: 12
Analog Output Channels: 2 x Stereo Master Output
2 x Stereo Control Room/Monitor Output
2 x Mono Aux Send Output
1 x Mono FX Send Output
1 x Stereo Headphone Output
Mix Routing: 1 x Stereo Main Mix per Mono Input Channel, Stereo Input Channel, Aux Bus/Subgroup
Faders: 13 x 2.4" / 60 mm Channel Fader
1 x 2.4" / 60 mm FX Fader
2 x 2.4" / 60 mm Bus/Subgroup Fader
1 x 2.4" / 60 mm Master Fader
Meters Main Meter:
2 x 12-Segment LED
Meter Range: -30 dB to +20 dB Peak/Clip
Gain/Trim Range: +60 dB
Dynamic Processing: None
EQ: 3-Band Semi-Parametric
3-Band Shelving/Notch/Peak
EQ Parameters Mono Channels:
High: ± 15 dB at 12 kHz
Mid: ± 15 dB at 100 Hz to 8 kHz
Low: ± 15 dB at 80 Hz
Stereo Channels:
High: ± 15 dB at 12 kHz
Mid: ± 15 dB at 2.5 kHz

Low: ± 15 dB at 80 Hz

Filters Input Channels:

1 x High-Pass: 100 Hz

Solo/Mute Solo per Input Channel

Mute per Input Channel, Bus, FX Bus, Master

Built-In Effects: Yes

Sample Rates: 96 kHz

Bit Depth: 24-Bit

Connectivity

Analog Inputs: 12 x XLR 3-Pin Balanced Mic Input

8 x 1/4" TRS Balanced/Unbalanced Line Input

4 x 1/4" TRS Unbalanced Line Insert

2 x 1/4" TRS Balanced/Unbalanced Hi-Z Input

10 x 1/4" TRS Balanced/Unbalanced Stereo Line Input (4 Stereo Pairs)

1 x 1/4" TRS Footswitch Input

Analog Outputs: 2 x XLR 3-Pin Balanced Stereo Main Output (1 Stereo Pair)

2 x 1/4" TRS Balanced/Unbalanced Stereo Main Output (1 Stereo Pair)

2 x 1/4" TRS Balanced/Unbalanced Stereo Monitor Output (1 Stereo Pair)

2 x 1/4" TRS Balanced/Unbalanced Mono Aux/Monitor Output

1 x 1/4" TRS Balanced/Unbalanced FX Send

Phantom Power: +48 V (Applied to All Inputs)

Digital I/O: None

MIDI I/O: None

USB: 1 x USB-B (Audio Playback, Host Connection, Recording)

Recording

Max Multitrack Recording: 18 Tracks

Media Support: SD

OS Compatibility: macOS

Windows

*As of April, 2022: Check with manufacturer for the most up-to-date compatibility

Power

AC Input Power: 100 to 240 VAC, 50 / 60 Hz

AC Power Connector: 1 x IEC Input

Power Consumption: 45 W

Physical

Rack Mountable: Yes

Dimensions: 475 x 355.6 x 114.3 mm

Weight: 6.9 kg