

## MACKIE Onyx16 - Mikseta bez snage/Pasivna mikseta

MACKIE Onyx16, Mikseta bez snage/Pasivna mikseta

Šifra: 16848

Kategorija proizvoda: Studijske Miksete

Proizvođač: MACKIE

Cena: **68.280,00** rsd

**Onyx16** ispunjen je sjajnim sadržajima, tu su Perkins ekvilajzer u britanskom stilu, moćni DSP efekti, displej u punom koloru, kao i integrisano stereo snimanje i plejbek sa SD kartice. Mikser nudi end-to-end performanse ultra niskog šuma, koje zahteva rad studijskih profesionalaca.

### Klasičan zvuk, moderne performanse

Višestruko nagrađivana Onyx pretpojačala donose do 60 dB jačine.

Premijum analogna kola isporučuju studijski kvalitet zvuka i šum drže na minimumu.

### Direktno stereo (2x2) snimanje i plejbek na SD karticu

Višekanalno (24x4) snimanje u visokoj rezoluciji (96 kHz / 24-bit), za Mac/PC via USB

Direktno na SD kartu (2x2) stereo snimanje i plejbek

Četvorokanalni, dodeljivi USB return (2 stereo para)

Pošaljite vaš Main Mix na USB jednostavno, putem prekidača

Displej u punom koloru za sve studio komande, plus interfejs kontrolisan jednim potencijetrom

Jednostavna navigacija parametara efekata, onboard SD snimanje i plejbek

Vizualno pregledajte fajlove na SD kartici putem ugrađenog displeja

Dodeljivi (fizički) dugmići za komande: Previous, Next, Record, Play/Pause

Sačuvajte do 6 korisničkih presetova efekata za brz i lak odziv

Profesionalni procesor efekata visoke rezolucije

Korišćenje integrisanih efekata za lajv performanse, strimovanje i drugo.

Reverb, Delay, Chorus, itd.

Postignite savršen zvuk uz podesive parametre i dodeljive ekvilajzere

### Bluetooth Streaming for Wireless Audio Streaming

Pair your Bluetooth enabled device and stream audio directly to a channel on the mixer  
Streamed audio can be routed to Aux Sends and the Main Mix

### **Powerful Mixing Toolkit**

3-band Perkins EQ with on/off hard-bypass switch on all channels  
Hi-Z switches allows direct connection of guitars, basses, and other instruments  
100 Hz low-cut filter and 48V phantom power on all mic channels  
Stereo 3.5mm input and Bluetooth streaming  
Stereo line inputs  
Aux/Monitor outputs with dedicated per-channel send control  
Dedicated Control Room outputs  
Headphone output with dedicated level control  
L/R Assign switch per channel  
12-segment stereo meters  
Overload indicators on all channels  
PFL/AFL channel solo  
Footswitch input for FX Mute (footswitch not included)  
Powerful Software and Plugins  
Waveform OEM recording software and plugin bundle  
DAW Essentials Bundle for Waveform OEM, with 16 powerful plugins like Equalizer, Compressor, Reverber8, and Limiter  
Rugged Chassis and Professional Design  
Backlit mute and solo buttons provide a positive tactile feel and clear visual feedback

### **Mackie ONYX16 Specs**

Mixer  
Number of Analog Input Channels: 18 (8 Mono / 5 Stereo)  
Number of Mic Preamps: 12  
Analog Output Channels: 2 x Stereo Master Output  
2 x Stereo Control Room/Monitor Output  
2 x Mono Aux Send Output  
1 x Mono FX Send Output  
1 x Stereo Headphone Output  
Mix Routing: 1 x Stereo Main Mix per Mono Input Channel, Stereo Input Channel, Aux Bus/Subgroup  
Faders: 13 x 2.4" / 60 mm Channel Fader  
1 x 2.4" / 60 mm FX Fader  
2 x 2.4" / 60 mm Bus/Subgroup Fader  
1 x 2.4" / 60 mm Master Fader  
Meters Main Meter:  
2 x 12-Segment LED  
Meter Range: -30 dB to +20 dB Peak/Clip  
Gain/Trim Range: +60 dB  
Dynamic Processing: None  
EQ: 3-Band Semi-Parametric  
3-Band Shelving/Notch/Peak  
EQ Parameters Mono Channels:  
High:  $\pm 15$  dB at 12 kHz  
Mid:  $\pm 15$  dB at 100 Hz to 8 kHz  
Low:  $\pm 15$  dB at 80 Hz  
Stereo Channels:  
High:  $\pm 15$  dB at 12 kHz  
Mid:  $\pm 15$  dB at 2.5 kHz  
Low:  $\pm 15$  dB at 80 Hz  
Filters Input Channels:  
1 x High-Pass: 100 Hz  
Solo/Mute Solo per Input Channel  
Mute per Input Channel, Bus, FX Bus, Master  
Built-In Effects: Yes

Sample Rates: 96 kHz

Bit Depth: 24-Bit

Connectivity

Analog Inputs: 12 x XLR 3-Pin Balanced Mic Input

8 x 1/4" TRS Balanced/Unbalanced Line Input

4 x 1/4" TRS Unbalanced Line Insert

2 x 1/4" TRS Balanced/Unbalanced Hi-Z Input

10 x 1/4" TRS Balanced/Unbalanced Stereo Line Input (4 Stereo Pairs)

1 x 1/4" TRS Footswitch Input

Analog Outputs: 2 x XLR 3-Pin Balanced Stereo Main Output (1 Stereo Pair)

2 x 1/4" TRS Balanced/Unbalanced Stereo Main Output (1 Stereo Pair)

2 x 1/4" TRS Balanced/Unbalanced Stereo Monitor Output (1 Stereo Pair)

2 x 1/4" TRS Balanced/Unbalanced Mono Aux/Monitor Output

1 x 1/4" TRS Balanced/Unbalanced FX Send

Phantom Power: +48 V (Applied to All Inputs)

Digital I/O: None

MIDI I/O: None

USB: 1 x USB-B (Audio Playback, Host Connection, Recording)

Recording

Max Multitrack Recording: 18 Tracks

Media Support: SD

OS Compatibility: macOS

Windows

\*As of April, 2022: Check with manufacturer for the most up-to-date compatibility

Power

AC Input Power: 100 to 240 VAC, 50 / 60 Hz

AC Power Connector: 1 x IEC Input

Power Consumption: 45 W

Physical

Rack Mountable: Yes

Dimensions: 475 x 355.6 x 114.3 mm

Weight: 6.9 kg