

## MACKIE Thump115S - Aktivni vufer

Šifra: 16860  
Kategorija proizvoda: Aktivni Subwooferi  
Proizvođač: MACKIE

**Cena: 95.880,00 rsd**



**Thump115S** ima dva "full-range" XLR ulazna i dva "high-pass" XLR izlazna, i dva "full-range" XLR izlaza. Tu je i varijabilna

crossover kontrola, polarni inverter, LED na prednjem panelu, kao i mono/stereo sumiranje za single- ili dual- subvufer upotrebu. Dva "cut-through" rukohvata nalaze se na gornjoj strani, za lako podizanje i prenošenje.

### **A True Workhorse for Gigging Professionals**

1400W Class-D amplifier is designed for ultrareliable, consistent performance  
15" high-performance woofer  
Built-Like-A-Tank to conquer every gig while lightweight for easy loading  
Frequency response: 36 to 200 Hz  
Max SPL: 131 dB

### **Voicing Modes**

Flat: Natural balance between deep bass and overall output  
Deep: Emphasizes ultra-low frequencies. Great for dance, rap, and electronic music  
Punch: Prioritizes highest possible output level. Great for bands and rock music  
Variable

### **Optimized for Your System**

Variable crossover frequency  
Polarity invert switch  
Defeatable front LED  
Stereo or mono summing for single- or dual-subwoofer deployment  
Variable level control (-6 to +6 dBu)  
Front LED On/Off

### **Versatile Inputs and Outputs**

Stereo XLR inputs  
Stereo full-range XLR outputs  
Stereo high-pass XLR outputs

## **Versatile Configuration Options**

Integrated M20-threaded pole mount

### **Mackie Thump115S Specs**

Configuration: Active Subwoofer

Enclosure: Type Bass-Reflex Subwoofer

Total Power Capacity: 1400 W Peak

Amplifier Class: Class-D

Drivers:

MF Driver None

LF Driver 1 x 15" / 381 mm Woofer

Performance

Frequency Response: 36 Hz to 200 Hz

Maximum SPL: 131 dB SPL

Connectivity

Audio I/O: 2 x XLR 3-Pin Female Balanced Line Input

4 x XLR 3-Pin Male Balanced Line Output

Network I/O: None

USB: None

Wireless Connectivity: None

Signal Processing

Crossover High-Pass: 80 to 160 Hz

EQ: None

Parametric EQ: None

Semi-Parametric EQ: None

Filters: None

Alignment Delay: None

Phase Adjustment -180 / 0°

Digital Signal Processing: Voicing Modes

Power

AC Input Power

Universal: 100 to 240 VAC, 50 / 60 Hz

AC Power Connector: 1 x IEC

Power Consumption: 75 W

Physical

Mounting: 1 x M20 Pole Socket (Top)

Handles: 1 x Each Side

Dimensions: 584.2 x 457.2 x 457.2 mm

Weight: 34 kg