

ART DUAL RDB - DI Box

Šifra: 16878
Kategorija proizvoda: DI Box i Phantom Power
Proizvođač: ART

Cena: **11.880,00** rsd

The unit features both 1/4" TRS phone and XLR inputs, and outputs microphone or instrument levels. Two variable input level controls allow for proper level staging at the source rather than anywhere else in the signal chain. Two high-quality isolation transformers prevent ground loops from occurring when connecting various systems together.

Dual 1/4" TRS and XLR balanced line level inputs
Transformer isolated XLR balanced microphone level outputs
Transformer isolated 1/4" TRS balanced instrument level outputs
20Hz to 20kHz frequency response
Variable level controls with mute
Channel 2 source-selectable between Channel 1 or Channel 2 input
Channel 2 output phase switch

ART DUAL RDB Specs

Type Passive
Input Connections 2 XLR
2 x 1/4" TRS phone
Output Connectors 2 XLR
2 x 1/4" TRS phone
Controls 2 x Variable Input Pad knobs
Frequency Response 20Hz to 20kHz, +/-0.5dB @ +4dBu
THD 0.01% typical @ 1kHz, +18dBu
<0.05% @ 100Hz, +18dBu
Crosstalk > 80dB (typical)
Power Not applicable
Dimensions 4.6 x 3.9 x 1.85" (117 x 99 x 47mm)
Weight 0.88 lb (0.4kg)
Specialties Insertion Loss
-20dB @100K load
-25dB @60Ω load
Packaging Info
Package Weight 1 lb
Box Dimensions (LxWxH) 13.4 x 6.6 x 0.4"