

## Pioneer XPRS122 - Aktivni zvučnik

Šifra: 17082

Kategorija proizvoda: Aktivne Zvučne Kutije

Proizvođač: Pioneer DJ

Cena: **107.880,00** rsd

### Powerful Class-D Amplification

The XPRS2 Series employs Class-D amplification with high output wattage for a powerful and premiere audio experience for performers and listeners alike. The XPRS122 full-range speaker features Class-D 2000W amplification.

### High-Quality and Robust Build

Pioneer DJ's all-new XPRS2 Series features a sleek all-black, protective plywood cabinet for performance in harsh indoor and outdoor environments. The series models all come with a durable handle to support system portability and handling during setup and take down. The XPRS2 Series also features rubber feet to create separation and shock absorption between surfaces.

### Four DSP Modes

Both of the XPRS2 full-range speakers contain four different DSP preset modes: Live, Music, Speech, and Floor Monitor to address the needs of different listening environments.

### XPRS122 Full-Range Speaker Design

The XPRS122 is the larger full-range speaker counterpart in Pioneer DJ's XPRS2 Series. Featuring a 12" woofer and 3" voice coil with a 1" exit compression driver and 1.75" voice coil, the speakers deliver comprehensive sound coverage across mid to large audiences and venues. Boasting a frequency response of 48 Hz to 20 kHz and a maximum SPL of 131 dB, the versatile full-range speaker delivers powerful sound built to thrive in even the harshest of sound environments such as a live DJ set.

### Pioneer DJ XPRS122 Specs

Configuration Active 2-Way

Enclosure Type Bass-Reflex Loudspeaker

Total Power Capacity 2000 W Peak

1000 W Program

500 W RMS

Amplifier Class Class-D

Drivers

HF Driver 1 x 1" / 25.4 mm Titanium Compression Driver

HF Voice Coil 1.75" / 4.45 cm

LF Driver 1 x 12" / 30.5 cm Woofer

LF Voice Coil 3" / 7.6 cm

Performance

Frequency Response 48 Hz to 20 kHz -10 dB

Maximum SPL 131 dB (Peak)

Protections Overload, Signal Limiter, Thermal

Connectivity

Audio I/O 1 x Combo XLR-1/4" 3-Pin Female Balanced/Unbalanced Mic/Line Input

1 x Combo XLR-1/4" 3-Pin Female Balanced/Unbalanced Line/Hi-Z Input

1 x 1/8" / 3.5 mm TRS Female Unbalanced Line Input  
1 x XLR 3-Pin Balanced Mix Output  
Network I/O None  
USB None  
Wireless Connectivity None  
Signal Processing  
EQ None  
Parametric EQ None  
Semi-Parametric EQ None  
Filters None  
Dynamic Processing Compression, Limiter  
Phase Adjustment None  
Digital Signal Processing Voicing Modes  
Power  
AC Input Power 110 to 240 VAC, 50 / 60 Hz (T 10 A L 250 V)  
AC Power I/O 1 x IEC Input  
Power Consumption 800 W  
Physical  
Mounting 1 x 1.4" / 35 mm Pole Socket (Bottom)  
10 x M10 Fly Point  
Handles 1 x Each Side  
Construction Material Plywood  
Dimensions 25.1 x 14.3 x 13.8" / 637.5 x 363.2 x 350.5 mm  
Weight 44.5 lb / 20.2 kg