

Neutrik NC3MD-LX type unknown

Neutrik NC3MD-LX

Šifra: 17089
Kategorija proizvoda: Konektori
Proizvođač: Neutrik

Cena: **720,00** rsd

Features & Benefits

All metal housing offers best overall RF protection and electromagnetic shielding
Duplex ground contact for excellent contact integrity between chassis and cable connector
Male connector's retention bar replaces plastic design with all metal version improving pull-out force
Larger solder contacts for easier termination
Optional connection to easily join pin1 to chassis ground
D-style housing provides installation compatibility with industry standard D mounting dimensions

Technical Information

Product
Title NC3MD-LX
Connection Type XLR
Gender male
Electrical
Capacitance between contacts ≤ 4 pF
Contact resistance ≤ 5 m Ω
Dielectric strength 1,5 kVdc
Insulation resistance > 10 G Ω (initial)
Rated current per contact 16 A
Rated voltage < 50 V
Mechanical
Insertion force ≤ 20 N
Withdrawal force ≤ 20 N
Lifetime > 1000 mating cycles
Wiresize max. 2.5 mm²
Wiresize max. 14 AWG
Wiring Solder contacts
Locking device Latch lock
Chassis shape D
Material
Contact plating 2 μ m Ag over 2 μ m Ni
Contacts Brass (CuZn35Pb2)
Insert Polyamide (PA66)
Locking element Steel Ck67
Shell Zinc diecast (ZnAl4Cu1)
Shell plating Nickel
Environmental
Flammability UL 94 V-0
Standard compliance IEC 61076-2-103
Protection class IP 40
Solderability Complies with IEC 68-2-20

Temperature range -30 °C to +80 °C