

## Neutrik NC3MD-LX

Šifra: 17089  
Kategorija proizvoda: Konektori  
Proizvođač: Neutrik

**Cena: 600,00 rsd**



### Features

All metal housing offers best overall EMI protection and electromagnetic shielding  
Duplex ground contact for excellent contact integrity between chassis and cable connector  
Male connector's retention bar replaces plastic design with all metal version improving pull-out force  
Larger solder contacts for easier termination  
Optional connection to easily join pin1 to chassis ground  
D-style housing provides installation compatibility with industry standard D mounting dimensions

### Technical Information

Product  
Title NC3MD-LX  
Connection Type XLR  
Gender male  
Electrical  
Capacitance between contacts  $\leq 4$  pF  
Contact resistance  $\leq 5$  m $\Omega$   
Dielectric strength 1,5 kVdc  
Insulation resistance  $> 10$  G $\Omega$  (initial)  
Rated current per contact 16 A  
Rated voltage  $< 50$  V  
Mechanical  
Insertion force  $\leq 20$  N  
Withdrawal force  $\leq 20$  N  
Lifetime  $> 1000$  mating cycles  
Wiresize max. 2.5 mm<sup>2</sup>  
Wiresize max. 14 AWG  
Wiring Solder contacts  
Locking device Latch lock  
Chassis shape D  
Material  
Contact plating 2  $\mu$ m Ag over 2  $\mu$ m Ni  
Contacts Brass (CuZn35Pb2)  
Insert Polyamide (PA66)  
Locking element Steel Ck67  
Shell Zinc diecast (ZnAl4Cu1)  
Shell plating Nickel  
Environmental  
Flammability UL 94 V-0  
Standard compliance IEC 61076-2-103  
Protection class IP 40  
Solderability Complies with IEC 68-2-20

Temperature range -30 °C to +80 °C