

Neutrik NL4MPXX - ugradni SpeakON

Neutrik NL4MPXX - ugradni SpeakON

Šifra: 17091
Kategorija proizvoda: Konektori
Proizvođač: Neutrik

Cena: **396,00** rsd

Features & Benefits

IEC 61984 certified > IEC 62368-1 compliant Glass reinforced V-0 materials make it extremely robust and dependable
Precise keyway for secure mating
Accurate twist lock latching system
Metal insert in locking area
Airtight design - optimized for speaker applications

Technical Information

Product
Title NL4MPXX
Gender male
Electrical
Contact resistance $\leq 2 \text{ m}\Omega$
Dielectric strength 2.8 kVac
Insulation resistance $>0.1 \text{ G}\Omega$ (after dampheat)
Rated current per contact 25 A rms continuous (audio rating significantly higher, depending on signal)
Rated voltage 250 V ac
Attention speakON is NOT to be used as an AC mains or power supply connector!
Mechanical
Lifetime > 5000 mating cycles
Termination 3/16" flat tabs (e.g. NLFASTON)
Locking device Quick Lock
Chassis shape D
Layout standard hole position, thru holes
Material
Contact plating Ag
Locking element Stainless Steel
Shell Polyamide (PA 6.6)
Contacts Copper Alloy
Environmental
Flammability UL94 V-0
Temperature range $-30 \text{ }^\circ\text{C}$ to $+80 \text{ }^\circ\text{C}$