

Neutrik NL4MPXX - ugradni SpeakON

## Neutrik NL4MPXX - ugradni SpeakON

Šifra: 17091  
Kategorija proizvoda: Konektori  
Proizvođač: Neutrik

Cena: **396,00** rsd

### Features & Benefits

IEC 61984 certified > IEC 62368-1 compliant Glass reinforced V-0 materials make it extremely robust and dependable  
Precise keyway for secure mating  
Accurate twist lock latching system  
Metal insert in locking area  
Airtight design - optimized for speaker applications

### Technical Information

Product  
Title NL4MPXX  
Gender male  
Electrical  
Contact resistance  $\leq 2 \text{ m}\Omega$   
Dielectric strength 2.8 kVac  
Insulation resistance  $>0.1 \text{ G}\Omega$  (after dampheat)  
Rated current per contact 25 A rms continuous (audio rating significantly higher, depending on signal)  
Rated voltage 250 V ac  
Attention speakON is NOT to be used as an AC mains or power supply connector!  
Mechanical  
Lifetime  $> 5000$  mating cycles  
Termination 3/16" flat tabs (e.g. NLFASTON)  
Locking device Quick Lock  
Chassis shape D  
Layout standard hole position, thru holes  
Material  
Contact plating Ag  
Locking element Stainless Steel  
Shell Polyamide (PA 6.6)  
Contacts Copper Alloy  
Environmental  
Flammability UL94 V-0  
Temperature range  $-30 \text{ }^\circ\text{C}$  to  $+80 \text{ }^\circ\text{C}$