

Mackie EM-93MK - Set za live stream

MACKIE EM-93MK - Set za live stream

Šifra: 17103

Kategorija proizvoda: Studio Paketi

Proizvođač: MACKIE

Cena: **13.800,00** rsd

The condenser microphone provides clear audio and comes with two windscreens, furry and foam, while the LED video light includes a diffuser for adjusting light intensity and adding a nice soft glow to your shots. With three cold shoe mounts on the LED light, setup is easy, and the convenient LCD display lets you dial in the perfect light temperature based on your available ambient light.

Versatile and Simple

The EM-93MK kit is designed to take the hassle out of content creation so that you can simply grab your phone, some snacks, and focus on your work. In the box, you get the cardioid EM-93M ultracompact microphone with both furry and foam windscreens, a variable temperature LED video light with diffuser, universal phone mount, handheld tripod, extension pole, plus a carry bag. Not only does it work great on a desk, but it's also just as easy to take with you on the go, even handheld.

One Kit, Endless Content

Awesome audio, lighting, smartphone stand, good to go. All nestled neatly in their custom case. From yoga videos to live streams, its incredibly easy to get great sound and a good look with the EM-93MK vlogger kit. You can even adapt the LED light to the ambient light in the room with its variable color temperature. And the included diffuser adds a nice soft glow to your shot.

Mackie EM-93MK Specs

Microphone

Primary Applications Web-Streaming, Recording to Mobile Device, ENG (Electronic News Gathering), Audio for Video, Location Sound, Field Recording

Form Factor Camera-Mount / Mobile Device Mic

Intended Sound Sources Vocals, Speech/Voice Over, Room Ambiance

Sound Field Mono

Operating Principle Pressure Gradient

Capsule 1 x Condenser

Polar Pattern Cardioid

Orientation End Address

Circuitry Solid-State

Pad None

High-Pass Filter None

Tone Adjustment None

Gain Adjustment None

On-Board Controls None

Windscreen Windsock/Windjammer (Included)

Foam (Included)

Performance

Frequency Range 35 Hz to 20 kHz

Impedance 680 Ohms

Sensitivity -42 dB

Signal-to-Noise Ratio 68 dB

Connectivity

Output Connectors (Analog) 1 x 1/8" / 3.5 mm TRS Female (on Mic)

1 x 1/8" / 3.5 mm TRS Male (on Detachable Cable)

1 x 1/8" / 3.5 mm TRRS Male (on Detachable Cable)

Headphone Connector None

Power

Operating Voltage Not Specified by Manufacturer

Physical

Color Black

Mounting Camera/Shoe-Mount (Included)

Mounting Thread Size Included Mount Has No Threading

Included Case None

Included Filters None

Certifications WEEE, ICES-003 (B), FCC Part 15

*as per Manufacturer

Dimensions H: 3.1 x W: 0.9" / H: 7.9 x W: 2.3 cm

Weight 1.4 oz / 40 g